



**Vadlīnijas
ISO 20022 XML ziņojumu "klients–banka" un "banka-klients" posmā
ieviešanai Latvijā**

**Apstiprinātas Latvijas Komercbanku asociācijas
Padomes 20.06.2014. sēdē (protokols Nr.3-2/6)**

**Grozījumi apstiprināti Latvijas Komercbanku asociācijas
Padomes 02.02.2018. sēdē (protokols Nr.3-2/2)**

**Grozījumi apstiprināti Latvijas Finanšu nozares asociācijas
Padomes 03.10.2018. sēdē (protokols Nr.3-2/10, 11§)**

Saturs

Ievads	3
1. Maksājumu ierosināšanas ziņojums	4
Maksājuma ierosināšanas ziņojumu satura apraksts	4
Ziņojuma elementi	5
Specifiskas informācijas ievadīšana	25
AMK koda norādīšana	25
EKK norādīšana	26
Rubļu maksājums uz Krieviju	27
Dolāru maksājums uz ASV	29
Maksājumu paraugi	30
2. Maksājumu statusa atbildes ziņojums	38
Maksājuma statusa ziņojumu satura apraksts	38
Ziņojuma elementi	39
Maksājumu statusa paraugs	43
3. Konta pārskata ziņojums	46
Konta pārskata ziņojuma satura apraksts	46
EKK kodu lietošanas piemērs Valsts kasē	72
Konta pārskata ziņojuma paraugs	73
Piemērs camt.060.001.03 ziņojuma izmantošanai	77
4. Konta izraksta ziņojums	78
Konta izraksta ziņojuma satura apraksts	78
EKK kodu lietošanas piemērs Valsts kasē	107
Konta pārskata ziņojuma paraugs	108
Piemērs camt.060.001.03 ziņojuma izmantošanai	112

Ievads

Dokumenta mērķis ir sniegt vadlīnijas ISO 20022 XML izveidei atbilstoši Latvijas tirgus vajadzībām, lai viennozīmīgi un nepārprotami nodotu un saņemtu finanšu informāciju „klients – banka” un “banka-klients” posmā Latvijas teritorijā.

Dokuments satur aprakstu par ziņojuma elementiem, kuri ir nepieciešami, lai apmainītos ar finanšu datu informāciju atbilstoši formāta prasībām. Ziņojuma elementi, kuri nav nepieciešami minētās informācijas atspoguļošanai Latvijas teritorijā, nav iekļauti šajā formāta aprakstā.

Dokuments ir jāaplūko kompleksi ar ISO 20022 XML ziņojumu standarta 2.versiju (konta pārskata un konta izraksta gadījumā) un 3.versiju, nemot vērā ISO noteikumus, kuri netiek pilnībā atkārtoti šajā aprakstā, taču tiek ievēroti veidojot ziņojumus.

Latvijas tirgus vajadzībām izstrādātajās vadlīnijās tiek ietverti šādi ziņojumi:

- maksājuma ierosināšana – pan.001.001.03;
- maksājuma statuss – pan.002.001.03;
- konta pārskats – camt.052.001.02;
- konta izraksts – camt.053.001.02.

Vadlīniju izstrādē izmantoti:

1) Eiropas Maksājumu padomes (European Payments Council, EPC) Vadlīnijas SEPA kredīta pārvedumu (SCT- SEPA Credit Transfer) ieviešanā klients-banka posmā, pieejams: http://www.europeanpaymentscouncil.eu/knowledge_bank_detail.cfm?documents_id=537 (spēkā no 17.11.2012.);

2) ISO 20022 Cash Management v2 Common Implementation MIGs (apstiprināts 01.07.2011.), pieejams: http://www.swift.com/corporates/cgi/resource_centre?lang=en;

3) Eiropas Maksājumu padomes Vadlīnijas SEPA kredīta pārvedumu ieviešanā klients-banka posmā versija 1.0 (SEPA Credit Transfer Scheme customer-to-bank implementation guidelines Version 1.0), pieejams: <https://www.europeanpaymentscouncil.eu/sites/default/files/KB/files/EPC132-08%20SCT%20C2B%20IG%202017%20V1.0.pdf> (spēkā no 19.11.2017.)

Vadlīniju dokuments ir izstrādāts sadarbojoties Latvijas bankām Latvijas Komercbanku asociācijā.

1. Maksājumu ierosināšanas ziņojums

pain.001.001.03

Maksājuma ierosināšanas ziņojumu satura apraksts

Ziņojums satur divus obligātos blokus: Galvene (Header) un Maksājumu informācija (Payment Information)

Galvene (Header): Šis bloks tiek norādīts tikai vienu reizi un satur faila identificējošus elementus – maksājuma identifikators, ziņojuma izveides datums un laiks, maksājuma iniciējošā puse.

Maksājumu informācija (Payment Information): Failā var būt norādīts viens (vai vairāki) maksājumu bloki. Šis bloks satur elementus, pēc kuriem tiek identificēts maksātājs (Debtors)- Debitora knts, Maksājuma tips, maksājuma izpildes datums. Tāpat šajā blokā ir informācija par maksājumiem (Credit Transfers), kas satur informāciju par maksājuma saņēmēju, saņēmēja banku, pārskaitījuma summu un maksājuma informāciju.

Zemāk parādītajā tabula aprakstīti ziņojumos izmantotie lauki sekojošā formātā:

Ind.	Or.	Mult.	Ziņojuma elements	<XML tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
		[1..1]	+ Message root				

Ind. – Ziņojuma elementa numurs. Numurs atbilst ISO 20022 XML Ziņojumu aprakstam, kurš ir atrodams vietnē www.iso20022.org zem "Catalogue of ISO 20022 messages" ar atsauci "pain.001.001.03".

Or. – Norāda uz izvēlni. Ziņojumā var tikt iekļauts viens vai otrs elements.

Mult. – Norāda uz elementa izmantošanas obligātumu un šī elementa parādīšanās biežumu. Iespējamās vērtības un to nozīme:

- [1..1] – Elements ir obligāts un var tikt norādīts vienu reizi;
- [1..n] - Elements ir obligāts un var tikt norādīts vienu vai vairākas reizes;
- [0..1] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts tikai vienu reizi;
- [0..n] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts vienu vai vairākas reizes.

Ziņojuma elements – Elementa nosaukums atbilstoši ISO 20022 XML

XML tags – Atbilstošā elementa XML tags ziņojumā

Tips – XML tagā ievadītās informācijas apraksts

Lietojums – Papildus piezīmes par lauka lietošanu. Ja šī piezīme ir augstāka līmeņa laukam, tā attiecās arī uz visiem šī lauka apakšlaukiem.

- Individuāli – Banka nenoraida maksājumu, taču laukā ievadīto informāciju izmanto pēc saviem ieskatiem vai saskaņā ar iepriekš panāktu vienošanos ar klientu.
- SEPA – Laiks tiek izmantots tikai SEPA maksājumiem

Komentāri – Papildu komentāri par lauka aizpildīšanu.

Ziņojuma elementi

Galvene - Header

Ind.	Or	Mult	Ziņojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
1.0		[1..1]	+GroupHeader	<GrpHdr>	Component			
1.1		[1..1]	++MessageIdentification	<MsgId>	Max35Text		Unikāls ziņojuma identifikators, ko piešķir ziņojuma radītājs	Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message. Usage: The account servicing institution has to make sure that MessageIdentification is unique per account owner for a pre-agreed period.
1.2		[1..1]	++CreationDateTime	<CreDtTm>	ISODateTime		Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss, piemēram: 2012-11-21T09:10:49)	Date and time at which the message was created (DDDD-MM-DDThh:mm:ss, example: 2012-11-21T09:10:49).
1.6		[1..1]	++NumberOfTransactions	<NbOfTxns>	Max15NumericText		Kopējais maksājumu skaits failā	Total amount of payments in file
1.7		[1..1]	++ControlSum	<CtrlSum>	Decimal Number		Kopējā maksājumu summa (neatkarīgi no valūtas). Piemērs 100EUR; 60USD; 50GBP- lauka vērtība 210	Total sum of all transaction amounts (regardless of currency). Exmaple: 100EUR; 60USD; 50GBP- value should read as 210
1.8 +		[1..1]	++Initiating Party	<InitgPty>	Party Identification Component	Individuāli	Informācija par maksājumu iniciētāju (var būt pats maksātājs, vai arī viņa reprezentējošā persona)	Information about party that initiates payment This can either be the debtor or the party that initiates the credit transfer on behalf of the debtor.
9.1.0		[0..1]	+++Name	<Nm>	Max140Text		Vārds/nosaukums vai cita informācija, kas neapšaubāmi identificē maksājuma iniciatoru.	Name by which a party is known and which is usually used to identify that party
9.1.12		[0..1]	+++Identification	<Id>	Choice Component		Unikāls puses identifikators (ID numurs, personas kods, reģistrācijas numurs u.t.t.).	Unique and unambiguous identification of a party
9.1.13	{Or}	[1..1]	++++OrganisationIdentification	<OrgId>	Component		Organizācijas Identifikators	Unique and unambiguous way to identify an organisation
9.1.14		[0..1]	+++++BICOrBEI	<BICOrBEI>	Identifier			
9.1.15		[0..n]	+++++Other	<Othr>	Component			
9.1.16		[1..1]	++++++Identification	<Id>	Max35Text		Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or Tax Payer number
9.1.17		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.18		[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis laiks	Name by which a party is known and which is usually used to identify that party.

						satur TXID. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.21	Or)	[1..1]	+++++PrivatIdentification	<PrvtId>	Component	Privātpersonas identifikators	Unique and unambiguous identification of a person, e.g. passport
9.1.27		[0..n]	+++++Other	<Othr>	Component		
9.1.28		[1..1]	++++++Identification	<Id>	Max35Text	Privātpersonas personas kods	Private personal code
9.1.29		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
9.1.30		[1..1]	++++++Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis laiks satur NIDN. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Name of the identification scheme, If personal code is used, NIDN is displayed Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code

Maksājumu informācija

Ind.	Or.	Mult .	Zinojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.0		[1..n]	+PaymentInformation	<PmtInf>	Component		Maksājumu informācijas bloks	Payment information
2.1		[1..1]	++PaymentInformation Identification	<PmtInfId>	Max35Text		Unikāls maksājuma bloka identifikators (piešķir maksājumu iniciators)	Unique identification, as assigned by a sending party,
2.2		[1..1]	++PaymentMethod	<PmtMtd>	Code		Maksājumu metodes kods. Laukā tiek norādīts tikai kods TRF – Kredīta pārvedumi	Specifies the means of payment that will be used to move the amount of money. <i>Usage:</i> Only TRF (Credit Transfer) should be used.
2.3		[0..1]	++Batch Booking	<BtchBookg>	Indicator	Individuāli	Lauks norāda, ka zemāk iesniegtie maksājumi ir jāizpilda kā vienas pakas maksājumi.	Identifies that batch entry for the sum of the amounts of all transactions within the group of a message is requested. <i>Usage:</i> Batch booking is used to request and not order a possible batch booking
2.4		[1..1]	++NumberOfTransactions	<NbOfTxs>	Max15NumericText		Maksājumu skaits konkrētā <PmtInf> sadāļā.	Number of individual transactions contained in the payment information <PmtInf> group.
2.5		[1..1]	++ControlSum	<CtrlSum>	Decimal Number		Maksājumu kopsumma konkrētā <PmtInf> sadāļā, neatkarīgi no valūtas.	Total of all individual amounts included in the group, irrespective of currencies
2.6		[0..1]	++PaymentTypeInformation	<PmtTpInf>	Component		Elementu kopums kas norāda maksājuma tipu/prioritāti.	Total of all individual amounts included in the group, irrespective of currencies

2.7		[0..1]	+++Instruction Priority	<InstrPrty>	Code	Individuāli	Norāda uz Maksājumu prioritāti konkrētā <PmtInf> sadalā. Atļautie kodi: HIGH - Augsta prioritāte NORM - parasta prioritāte Allowed codes: HIGH – high priority; NORM – normal priority	Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.
2.8		[0..1]	+++ServiceLevel	<SvcLvl>	Choice Component	Individuāli		
2.9	{Or	[1..1]	++++Code	<Cd>	Code		Maksājumu prioritātes kods no http://www.iso20022.org/external_code_list.page saraksta ExternalServiceLevel1Code	Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. http://www.iso20022.org/external_code_list.page
2.11		[0..1]	+++LocallInstrument	<LoclInstrm>	Choice Component		Nosaka maksājuma izpildes nosacījumus konkrētā <PmtInf> sadalā. Ja šī informācija aizpildīta arī zemākā līmenī, laiks tiek ignorēts.	Defines criteria of payment execution in particular <PmtInf> component. If this information is also displayed in lower level, then tag is ignored
2.12	{Or	[1..1]	++++Code	<Cd>	Code	Individuāli	Maksājumu prioritātes kods no http://www.iso20022.org/external_code_list.page saraksta ExternalLocallInstrument1Code	Specifies the local instrument, as published in an external local instrument code list http://www.iso20022.org/external_code_list.page
2.13	Or}	[1..1]	++++Proprietary	<Prtry>	Max35Text		Maksājuma prioritāte- NORM; HIGH; EXPR. Ja šī informācija aizpildīta arī zemākā līmenī (lauks 2.38), laiks tiek ignorēts. Allowed codes: NORM, HIGH, EXPR. If this information is also displayed in lower level (tag 2.38), then this tag is ignored.	Specifies the local instrument, as a proprietary code. Allowed codes: NORM, HIGH, EXPR. If this information is also displayed in lower level (tag 2.38), then this tag is ignored.
2.14		[0..1]	+++CategoryPurpose	<CtgyPurp>	Choice Component	Individuāli	Nosaka maksājuma mērķa kodu visiem maksājumiem konkrētā <PmtInf> sadalā. Ja šī informācija aizpildīta arī zemākā līmenī, laiks tiek ignorēts.	Specifies the high level purpose of the instruction in particular <PmtInf> component. If this information is also displayed in lower level, then this tag is ignored
2.15		[1..1]	++++Code	<Cd>	Code		Maksājuma mērķa kods. Atbilstošais kods no http://www.iso20022.org/external_code_list.page saraksta ExternalCategoryPurpose1Code Par izmantotajiem kodiem klients vienojās ar banku. Piemēram kods SALA lai norādītu ka maksājumi failā ir algu maksājumi Customer must agree on usage of codes with their bank. Example: SALA- used to indicate that there are salary payments in a file.	Category purpose, as published in an external category purpose code list http://www.iso20022.org/external_code_list.page Customer must agree on usage of codes with their bank. Example: SALA- used to indicate that there are salary payments in a file.
2.17		[1..1]	++RequestedExecutionDate	<ReqdExctnDt>	ISODate	Individuāli	Datums, kurā maksājumi jāizskaita no debetējamā konta. Katra banka individuāli nosaka, cik tālu nākotnē maksājuma rīkojumu var iesūtīt. Ja laukā norādīts pagātnes datums, tas automātiski tiek konvertēts uz tekošo dienu.	Date at which the initiating party requests the clearing agent to process the payment. Each bank individually decides the limits for future execution date. If there is a historic date displayed in the tag, then it is automatically converted to present date.

2.19 +		[1..1]	++Debtor	<Dbtr>	Party Identification Component	Individuāli	Dati par maksātāju. Maksātājs tiek identificēts pēc maksātāja konta numura (lauks. 2.20)	Party that owes an amount of money to the (ultimate) creditor. Debtor is identified according to debtor account (tag 2.20)
9.1.0		[1..1]	+++Name	<Nm>	Max140Text		Maksātāja nosaukums/vārds. SEPA maksājuma gadījumā lauka garums starpbanku posmā ir ierobežots līdz 70 zīmēm. Ja tiks norādīts lielāks zīmju skaits, banka saglabās tikai pirmās 70 zīmes. Maksātājs tiek identificēts pēc maksātāja konta numura (lauks. 2.20), ja individuāli ar banku nav panākta cita vienošanās.	Name of Debtor In case of SEPA payment length of the tag is limited to 70 characters. If longer value will be presented by customer, then only first 70 characters will be forwarded. Debtor is identified according to debtor account (tag 2.20), unless otherwise agreed with a bank.
9.1.1		[0..1]	+++PostalAddress	<PstlAdr>	Component		Pasta adrese	Information that locates and identifies a specific address, as defined by postal services
9.1.10		[0..1]	++++Country	<Ctry>	CountryCode		Vaļsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.11		[0..2]	+++++AdressLine	<AdrLine>	Max70Text			
9.1.12		[0..1]	+++Identification	<Id>	Choice Component		Viennozīmīgs maksātāja puses identifikators (ID numurs, personas kods, reģistrācijas numurs u.t.t.)	Unique and unambiguous identification of a party
9.1.13	{Or}	[1..1]	+++++OrganisationIdentification	<OrgId>	Component		Uzņēmuma identifikators	Unique and unambiguous way to identify an organisation
9.1.14		[0..1]	+++++BICOrBEI	<BICOrBEI>	Identifier			
9.1.15		[0..n]	+++++Other	<Othr>	Component			
9.1.16		[1..1]	++++++Identification	<Id>	Max35Text		Uzņēmuma reģistrācijas vai nodokļu maksātāja numurs	Registration number or Tax Payer number
9.1.17		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.18		[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis lauks satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	Name of the identification scheme, in a coded form as published in an external list. If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.21	Or}	[1..1]	++++PrivatIdentification	<PrvtId>	Component	Individuāli	Privātpersonas identifikators	Unique and unambiguous identification of a person, e.g. passport

9.1.22		[0..1]	+++++DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Component		Informācija par dzimšanas vietu un laiku	Date and place of birth of a person
9.1.23		[1..1]	+++++BirthDate	<BirthDt>	ISODate			ISODate
9.1.25		[1..1]	+++++CityOfBirth	<CityOfBirth>	Max35Text			
9.1.26		[1..1]	+++++CountryOfBirth	<CtryOfBirth>	CountryCode		Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.27		[0..n]	+++++Other	<Othr>	Component			
9.1.28		[1..1]	+++++Identification	<Id>	Max35Text		Privātpersonas personas kods	Private personal code
9.1.29		[0..1]	+++++SchemeName	<SchmeNm>	Choice Component			
9.1.30		[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis lauks satur NIDN. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Name of the identification scheme, If personal code is used, NIDN is displayed Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
2.20 +		[1..1]	++DebtorAccount	<DbtrAcct>	Component		Informācija par Maksātāja kontu, no kura tiks veikti darījumi	Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction
1.1.0		[1..1]	+++Identification	<Id>	Account Identification Component		Maksātāja konta identifikators	Identifier used internationally by financial institutions to uniquely identify the account of a customer
1.1.1		[1..1]	++++)IBAN	<IBAN>	IBANIdentifier		Konta numurs IBAN formātā. Šajā laukā tiek norādīts konta numurs no kura tiks veikti maksājumi	IBAN
1.1.11		[0..1]	+++Currency	<Ccy>	Currency Code	Individuāli	Maksātāja konta valūtas kods. <i>Piezīme:</i> Lietojams, kad debetējamais kants ir multivalūtu kants un ir nepieciešams norādīt konkrētu debetējamo valūtu.	Identification of the currency in which the account is held. <i>Usage:</i> Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account
2.21 +		[1..1]	++DebtorAgent	<DbtrAgt>	Financial Institution Identification Component		Finanšu institūcija kurai pieder debetējamais knts (Maksājumu pakalpojumu sniedzējs, kura veiks maksājumu)	Financial institution servicing an account for the debtor
6.1.0		[1..1]	+++FinancialInstitutionIdentification	<FinInstnId>	Component		Finanšu institūcijas identifikators	Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification

							scheme
6.1.1		[0..1]	++++BIC	<BIC>	BICIdentifier		Bankas BIC kods BIC
2.23 +		[0..1]	++UltimateDebtor	<UltmtDbtr>	Party Identification Component	SEPA	Galējā puse kas veic darījumu. Lauku aizpilda tikai gadījumā, ja atšķirīgs no Debitor. Ja šī informācija aizpildīta arī zemākā līmenī (lauks 2.70), lauks tiek ignorēts Ultimate party that owes an amount of money to the (ultimate) creditor. If this information is also displayed in lower level (tag 2.70), then this tag is ignored.
9.1.0		[0..1]	+++Name	<Nm>	Max140Text		Galējā maksātāja nosaukums/vārds. SEPA maksājuma gadījumā lauka garums starpbanku posmā ir ierobežots līdz 70 zīmēm. Ja tiks norādīts lielāks zīmju skaits, banka saglabās tikai pirmās 70 zīmes. Name of Ultimate Debtor In case of SEPA payment length of the tag is limited to 70 characters. If longer value will be presented by customer, then only first 70 characters will be forwarded.
9.1.1		[0..1]	+++PostalAddress	<PstlAdr>	Component		Galējā maksātāja pasta adrese Address of Ultimate Debtor
9.1.10		[0..1]	++++Country	<Ctry>	CountryCode		Galējā maksātāja rezidences valsts kods Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.11		[0..2]	+++++AdressLine	<AdrLine>	Max70Text		
9.1.12		[0..1]	+++Identification	<Id>	Choice Component		Galējā maksātāja identifikators Unique and unambiguous identification of a party
9.1.13	{Or}	[1..1]	+++++OrganisationIdentification	<OrgId>	Component		Uzņēmuma identifikators Unique and unambiguous way to identify an organisation
9.1.14		[0..1]	+++++BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	+++++Other	<Othr>	Component		
9.1.16		[1..1]	++++++Identification	<Id>	Max35Text		Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs Registration number or Tax Payer number
9.1.17		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
9.1.18		[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts nodokļu maksātāja kods, šis lauks satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code Name of the identification scheme, in a coded form as published in an external list. If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code

9.1.21	Or)	[1..1]	++++PrivateIdentification	<PrvtId>	Component		Privātpersonas identifikators	Unique and unambiguous identification of a person, e.g. passport
9.1.22		[0..1]	+++++DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Component		Informācija par dzimšanas vietu un laiku	Date and place of birth of a person
9.1.23		[1..1]	++++++BirthDate	<BirthDt>	ISODate			ISODate
9.1.25		[1..1]	++++++CityOfBirth	<CityOfBirth>	Max35Text			
9.1.26		[1..1]	++++++CountryOfBirth	<CtryOfBirth>	CountryCode		Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.27		[0..n]	+++++Other	<Othr>	Component			
9.1.28		[1..1]	++++++Identification	<Id>	Max35Text		Privātpersonas personas kods	Private personal code
9.1.29		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.30		[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis lauks satur NIDN. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Name of the identification scheme, If personal code is used, NIDN is displayed Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.33		[0..1]	+++CountryOfResidence	<CtryOfRes>	CountryCode		Galējā maksātāja rezidences valsts Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
2.24		[0..1]	++ChargeBearer	<ChrgBr>	Code		Norāda uz pusi kura sedz ar darījumu saistīto komisijas maksu. Maksājumiem uz EEZ valstīm atļauts tikai kods SLEV. Pārējiem maksājumiem atļauts viens no kodiem: DEBT- komisijas maksā maksātājs; SHAR- komisijas maksā dalīti; CRED- komisijas maksā saņēmējs. Pirms lietot kodu CRED precizējiet informāciju savā bankā. Ja lauks netiek aizpildīts, tas tiek uzskaitīts kā SHAR vai SLEV (ja vien zemākā līmenī (lauks 2.51) nav norādīts citādi) atkarībā no maksājuma tipa.	Specifies which party/parties will bear the charges associated with the processing of the payment transaction. Usage: Only SLEV is allowed in payments to EEA countries. For other payments the following codes are allowed: DEBT – BorneByDebtor; SHAR- Shared; CRED – BorneByCreditor. Consult with your bank prior to usage of CRED. If left empty, then either SHAR or SLEV is used (unless otherwise specified in lower level tag 2.51) according to payment type.
2.25 +		[0..1]	++ChargesAccount	<ChrgsAcct>	Component	Individuāli	Konts no kura tiek ieturēta komisijas maksa par zinojumā norādītajiem	Account used to process charges associated with a transaction.

						darījumiem. Par šī lauka izmantošanu Klients vienojas ar Banku	It must be agreed with bank prior to usage of this tag.
1.1.0	[1..1]	+++Identification	<Id>	Account Identification Component			
1.1.1	[1..1]	++++IBAN	<IBAN>	IBANIdentifier		Konta numurs IBAN formātā	IBAN
1.1.11	[0..1]	+++Currency	<Ccy>	Currency Code	Individuāli	<p>Valūta no kuras tiek ieturēta komisija.</p> <p><i>Piezīme:</i> Lietojams, kad debetējamais korts ir multivalūtu korts un ir nepieciešams norādīt konkrētu debetējamo valūtu.</p>	<p>Identification of the currency in which the account is held.</p> <p><i>Usage:</i> Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account</p>
2.27	[1..n]	++CreditTransferTransactionInformation	<CrdtTrfTxlnf>	Component		Precīza darījuma informācija. Katrs <CrdtTrfTxlnf> bloks satur informāciju par vienu unikālu maksājumu.	Set of elements used to provide information on the individual transaction(s) included in the message
2.28	[1..1]	+++PaymentIdentification	<PmtId>	Component		Maksājuma identifikācijas sadaļa	Set of elements used to reference a payment instruction
2.29	[0..1]	++++InstructionIdentification	<InstrId>	Max35Text		Unikāls transakcijas numurs. Laukā norādītais identifikators paredzēts, lai klients savā pusē identificētu maksājumu.	Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.
2.30	[1..1]	++++End-To-EndIdentification	<EndToEndId>	Max35Text	SEPA	Unikāls maksājuma identifikators, kas tiek nodots caur visu maksājuma kēdi nemainīts. Tieki pārsūtīti tālāk tikai SEPA maksājumos. Laukā norādītais identifikators paredzēts, lai klients-klients posmā identificētu maksājumu. Ne-SEPA maksājumos šis lauks tiek ignorēts.	Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. Used only in SEPA payments. In non-SEPA payments this tag is ignored.
2.31	[0..1]	+++PaymentTypeInformation	<PmtTpInf>	Component		Informācija, kas norāda uz maksājuma tipu. Ja tiek aizpildīta informācija kādā no šī lauka apakšlaukiem, attiecīgi tiek ignorēta informācija no lauka 2.6	Set of elements used to further specify the type of transaction. If any of the lower tags is filled then it overrides information that is displayed in tag 2.6
2.33	[0..1]	++++ServiceLevel	<SvcLvl>	Choice Component	Individuāli		
2.34	[1..1]	+++++Code	<Cd>	Code		Maksājumu prioritātes kods no http://www.iso20022.org/external_code_list.page saraksta ExternalServiceLevel1Code	Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list http://www.iso20022.org/external_code_list.page
2.36	[0..1]	++++LocalInstrument	<LocInstrm>	Choice Component			
2.38	[1..1]	+++++Proprietary	<Prtry>	Max35Text		Maksājuma prioritāte- NORM; HIGH; EXPR. Ja šī informācija aizpildīta arī augstākā līmenī (lauks 2.13), tad augstākā līmenē lauks tiek ignorēts.	Specifies the local instrument, as a proprietary code.
							Allowed codes: NORM, HIGH, EXPR.

							If this information is also displayed in upper level (tag 2.13), then that upper tag is ignored.
2.39	[0..1]	++++CategoryPurpose	<CtgyPurp>	Choice Component	Individuāli	Nosaka maksājuma mērķa kodu maksājumam Ja šī informācija ir aizpildīta tiek ignorēts augstāka līmena lauks.	Specifies the high level purpose of the instruction based on a set of pre-defined categories. If this tag is filled in upper level (tag 2.14), then that upper tag is ignored.
2.40	[1..1]	+++++Code	<Cd>	Code		Maksājuma mērķa kods. Atbilstošais kods no http://www.iso20022.org/external_code_list.page saraksta ExternalPurpose1Code Par izmantotajiem kodiem klients vienojās ar banku.	Category purpose, as published in an external category purpose code list http://www.iso20022.org/external_code_list.page Customer must agree on usage of codes with their bank.
2.42	[1..1]	+++Amount	<Amt>	Choice component		Darījuma summas sadaļa	Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.
2.43	[1..1]	++++InstructedAmount	<InstdAmt Ccy="AAA">	ActiveOrHistoric CurrencyAndAmount		Darījuma summa + valūta Piemērs, ja nepieciešams pārskaitīt 1000 EUR: <InstdAmt Ccy="LVL">1000</InstdAmt>	Amount of transaction + currency. <i>Example:</i> If 1000 EUR to be transferred: <InstdAmt Ccy="EUR">1000</InstdAmt>
2.47	[0..1]	+++ExchangeRateInformation	<XchgRateInf>	Component	Individuāli	Sadaļa par valūtas maiņas kursu+līgumu.	Set of elements used to provide details on the currency exchange rate and contract
2.48	[0..1]	++++ExchangeRate	<XchgRate>	BaseOneRate		Valūtas maiņas kurss.	The factor used for conversion of an amount from one currency to another. This reflects the price at which one currency was bought with another currency.
2.49	[0..1]	++++RateType	<RateTp>	Code		Norāda uz konvertācijas tipu SPOT- Spot valūtas vērtība; SALE - Tirdzus vērtība uz transakcijas brīdi; AGRD- Līgums starp pusēm (pamatvērtība pēc noklusējuma).	Specifies the type used to complete the currency Exchange. SPOT- Exchange rate applied is the spot rate; SALE - Exchange rate applied is the market rate at the time of the sale; AGRD- Exchange rate applied is the rate agreed between the parties (default value)
2.50	[0..1]	++++ContractIdentification	<CtrctId>	Max35Text		Norāde uz līgumu kas noslēgts starp maksātāju un banku (piemēram līguma numurs)	Unique and unambiguous reference to the foreign exchange contract agreed between the initiating party/ creditor and the debtor agent
2.51	[0..1]	+++ChargeBearer	<ChrgBr>	Code		Norāda uz pusī kura sedz ar darījumu saistīto komisijas maksu. Maksājumiem uz EEZ valstīm atļauts tikai kods SLEV. Pārējiem maksājumiem atļauts viens no kodiem: DEBT- komisijas maksā maksātājs; SHAR- komisijas maksā dalīti; CRED- komisijas maksā sanēmējs.	Specifies which party/parties will bear the charges associated with the processing of the payment transaction. <i>Usage:</i> Only SLEV is allowed in payments to EEA countries. For other payments the following codes are allowed:

						Pirms lietot kodu CRED precizējet informāciju savā bankā. Ja lauks netiek aizpildīts tas tiek uzskaņīts Kā SHAR vai SLEV (ja vien augstākā līmenī (lauks 2.24) nav norādīts citādi). Atkarībā no maksājuma tipa.	DEBT – BorneByDebtor; SHAR- Shared; CRED – BorneByCreditor. Consult with your bank prior to usage of CRED. If left empty, then either SHAR or SLEV is used (unless otherwise specified in upper level tag 2.24) according to payment type.
2.70 +	[0..1]	+++UltimateDebtor	<UltmtDbtr>	Party Identification Component	SEPA	Galējā puse kas veic darījumu. Lauku aizpilda tikai gadījumā ja atšķirīgs no Debitor. Ja šī informācija ir norādīta, augstākā līmenē lauks 2.23 tiek ignorēts. Piemērs: Uzņēmums veic viesnīcas rezervācijas apmaksu par savu darbinieku un šajā laukā norāda attiecīgā darbinieka rekvizītus.	Ultimate party that owes an amount of money to the (ultimate) creditor. Should only be filled if it is different from the information given in upper level tag 2.23. <i>Example:</i> A company pays for a hotel and indicates details of their employee who will be staying there.
9.1.0	[0..1]	++++Name	<Nm>	Max140Text		Galējā maksātāja nosaukums/vārds. SEPA maksājuma gadījumā lauka garums starpbanku posmā ir ierobežots līdz 70 zīmēm. Ja tiks norādīts lielāks zīmju skaits, banka saglabās tikai pirmās 70 zīmes.	Name of Ultimate Debtor In case of SEPA payment length of the tag is limited to 70 characters. If longer value will be presented by customer, then only first 70 characters will be forwarded.
9.1.1	[0..1]	++++PostalAddress	<PstlAdr>	Component		Galējā maksātāja pasta adrese	Address of Ultimate Debtor
9.1.10	[0..1]	+++++Country	<Ctry>	CountryCode		Galējā maksātāja valsts kods Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.11	[0..2]	+++++AdressLine	<AdrLine>	Max70Text			
9.1.12	[0..1]	++++Identification	<Id>	Choice Component		Galējā maksātāja identifikators	Unique and unambiguous identification of a party
9.1.13	{Or [1..1]}	+++++OrganisationIdentification	<OrgId>	Component		Uzņēmuma identifikators	Unique and unambiguous way to identify an organisation
9.1.14	[0..1]	++++++BICOrBEI	<BICOrBEI>	Identifier			
9.1.15	[0..n]	++++++Other	<Othr>	Component			
9.1.16	[1..1]	++++++Identification	<Id>	Max35Text		Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or Tax Payer number
9.1.17	[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.18	[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis	Name of the identification scheme, in a coded form as published in an external list.

						Iauks satur TXID. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.21	Or}	[1..1]	+++++PrivateIdentification	<PrvtId>	Component	Privātpersonas identifikators	Unique and unambiguous identification of a person, e.g. passport
9.1.22		[0..1]	++++++DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Component	Informācija par dzimšanas vietu un laiku	Date and place of birth of a person
9.1.23		[1..1]	++++++BirthDate	<BirthDt>	ISODate		ISODate
9.1.25		[1..1]	++++++CityOfBirth	<CityOfBirth>	Max35Text		
9.1.26		[1..1]	++++++CountryOfBirth	<CtryOfBirth>	CountryCode	Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.27		[0..n]	++++++Other	<Othr>	Component		
9.1.28		[1..1]	++++++Identification	<Id>	Max35Text	Privātpersonas personas kods	Private personal code
9.1.29		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
9.1.30		[1..1]	++++++Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis iauks satur NIDN. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Name of the identification scheme, If personal code is used, NIDN is displayed Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.33		[0..1]	+++CountryOfResidence	<CtryOfRes>	CountryCode	Galējā maksātāja rezidences valsts Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
2.71 +		[0..1]	+++IntermediaryAgent1	<IntrmyAgt1>	Financial Institution Identification Component	Individuāli Saņēmējbankas korespondentbanka	Agent between the debtor's agent and the creditor's agent. <i>Usage:</i> If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.
6.1.0		[1..1]	+++FinancialInstitutionIdentification	<FinInstnId>	Component	Unikāls finanšu institūcijas identifikators	Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification

							scheme
6.1.1		[0..1]	+++++BIC	<BIC>	BICIdentifier		Bankas Identifikācijas kods - BIC
6.1.2		[0..1]	+++++ClearingSystemMemberIdentification	<ClrSysMmbld>	Component		Klīringa sistēmas identifikatoris Information used to identify a member within a clearing system
6.1.3		[0..1]	++++++ClearingSystemIdentification	<ClrSysId>	Choice Component		
6.1.4	{Or}	[1..1]	++++++Code	<Cd>	Code		Klīringa sistēmas identifikatoris no http://www.iso20022.org/external_code_list.page saraksta ExternalClearingSystemIdentification1C ode Identification of a clearing system, in a coded form as published in an external list http://www.iso20022.org/external_code_list.page
6.1.5	Or}	[1..1]	++++++Proprietary	<Prtry>	Max35Text		
6.1.6		[1..1]	++++++MemberIdentification	<Mmbld>	Max35Text		Korespondentbankas identifikators noteiktajā klīringa sistēmā Identification of a member of a clearing system.
6.1.7		[0..1]	+++++Name	<Nm>	Max140Text		Korespondentbankas nosaukums Name of the Intermediary Agent (Bank)
6.1.8		[0..1]	+++++PostalAddress	<PstlAdr>	Component		Korespondentbankas pasta adrese
6.1.17		[0..1]	++++++Country	<Ctry>	CountryCode		Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code)
6.1.18		[0..2]	++++++AdressLine	<AdrLine>	Max70Text		
6.1.25		[0..1]	++++BranchIdentification	<Brnchld>	Component		
6.1.26		[0..1]	+++++Identification	<Id>	Max35Text		
6.1.27		[0..1]	+++++Name	<Nm>	Max140Text		
6.1.28		[0..1]	+++++PostalAddress	<PstlAdr>	Component		
6.1.37		[0..1]	++++++Country	<Ctry>	CountryCode		Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code)

							http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
6.1.38		[0..2]	+++++AdressLine	<AdrLine>	Max70Text		
2.72 +		[0..1]	+++IntermediaryAgentAccount1	<IntrmyAgt1Acct>	Cash Account Component	Individuāli	Saņēmējbankas korespondentbankas konta numurs Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.
1.1.0		[1..1]	++++Identification	<Id>	Account Identification Component		
1.1.1	{Or}	[1..1]	++++IBAN	<IBAN>	IBANIdentifier		IBAN
1.1.2	Or}	[1..1]	++++Other	<Othr>	Component		
1.1.3		[1..1]	++++++Identification	<Id>	Max34Text		
1.1.4		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
1.1.5		[1..1]	++++++Code	<Cd>	Code		
1.1.11		[0..1]	++++Currency	<Ccy>	Currency Code		
2.73 +		[0..1]	+++IntermediaryAgent2	<IntrmyAgt2>	Financial Institution Identification Component	Individuāli	Tiek izmantotas identiskas komponentes no lauka: +++IntermediaryAgent1 (lauks 2.71) The same lower tags as in 2.71 + are used here Agent between the debtor's agent and the creditor's agent. <i>Usage:</i> If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.
2.74 +		[0..1]	+++IntermediaryAgentAccount2	<IntrmyAgt2Acct>	Cash Account Component	Individuāli	Tiek izmantotas identiskas komponentes no lauka: +++IntermediaryAgentAccount1 (lauks 2.72) The same lower tags as in 2.72 are used here Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.
2.77 +		[0..1]	+++CreditorAgent	<CdtrAgt>	Financial Institution Identification Component		Informācija par saņēmēja banku (saņēmējbanka) Financial institution servicing an account for the creditor (Beneficiary bank)
6.1.0		[1..1]	++++FinancialInstitutionIdentification	<FinInstnId>	Component		Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme

6.1.1		[0..1]	+++++BIC	<BIC>	BICIdentifier		Sanēmēja bankas BIC kods Atsevišķos gadījumos BIC var būt nepieciešams saņēmējbankas identificēšanai	BIC
6.1.2		[0..1]	+++++ClearingSystemMemberIdentification	<ClrSysMmbld>	Component		Klīringa sistēmas identifikators	Information used to identify a member within a clearing system
6.1.3		[0..1]	++++++ClearingSystemIdentification	<ClrSysId>	Choice Component			
6.1.4		[1..1]	++++++Code	<Cd>	Code		Klīringa sistēmas identifikators no http://www.iso20022.org/external_code_list.page saraksta ExternalClearingSystemIdentification1Code	Identification of a clearing system, in a coded form as published in an external list http://www.iso20022.org/external_code_list.page
6.1.6		[1..1]	++++++MemberIdentification	<Mmbld>	Max35Text		Sanēmējbankas identifikators noteiktajā klīringa sistēmā	
6.1.7		[0..1]	+++++Name	<Nm>	Max140Text		Sanēmēja bankas nosaukums	Identification of a member of a clearing system.
6.1.8		[0..1]	+++++PostalAddress	<PstlAdr>	Component		Sanēmēja bankas pasta adrese	Name of the Intermediary Agent (Bank)
6.1.17		[0..1]	++++++Country	<Ctry>	CountryCode		Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	
6.1.18		[0..2]	++++++AdressLine	<AdrLine>	Max70Text			The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
2.78 +		[0..1]	+++CreditorAgentAccount	<CdtrAgtAcct>	Cash Account Component		Sanēmējbankas konta numurs korespondentbankā.	Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction
1.1.0		[1..1]	++++Identification	<Id>				
1.1.1	{Or	[1..1]	+++++IBAN	<IBAN>			IBAN	IBAN
1.1.2	Or}	[1..1]	+++++Other	<Othr>				
1.1.3		[1..1]	++++++Identification	<Id>				
2.79 +		[1..1]	+++Creditor	<Cdtr>	Party Identification Component		Informācijas bloks par maksājuma saņēmēju (Kreditors)	Party to which an amount of money is due (Beneficiary)
9.1.0		[1..1]	++++Name	<Nm>	Max140Text		Sanēmēja nosaukums/vārds uzvārds SEPA maksājuma gadījumā lauka garums starpbanku posmā ir ierobežots līdz 70 zīmēm. Ja tiks norādīts lielāks	Name of Debtor In case of SEPA payment length of the tag is limited to 70 characters. If longer value will be presented by customer, then only

						zīmju skaits, banka saglabās tikai pirmās 70 zīmes.	first 70 characters will be forwarded.
9.1.1		[0..1]	++++PostalAddress	<PstlAdr>	Component	Saņēmēja pasta adrese	Information that locates and identifies a specific address, as defined by postal services
9.1.10		[0..1]	+++++Country	<Ctry>	CountryCode	Saņēmēja rezidences valsts Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.11		[0..2]	+++++AdressLine	<AdrLine>	Max70Text		
9.1.12		[0..1]	++++Identification	<Id>	Choice Component	Saņēmēja identifikatora bloks (Piemēram personas kods, pasašs numurs, reģistrācijas kods u.t.t.)	Unique and unambiguous identification of a party
9.1.13	{Or}	[1..1]	+++++OrganisationIdentification	<OrgId>	Component	Uzņēmuma identifikators	Unique and unambiguous way to identify an organisation
9.1.14		[0..1]	++++++BICOrBEI	<BICOrBEI>	Identifier	SEPA	
9.1.15		[0..n]	++++++Other	<Othr>	Component		
9.1.16		[1..1]	++++++Identification	<Id>	Max35Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or Tax Payer number
9.1.17		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
9.1.18	{Or}	[1..1]	++++++Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis lauku satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	Name of the identification scheme, in a coded form as published in an external list. If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.19	Or}	[1..1]	++++++Proprietary	<Prtry>	Max35Text	Identifikācijas shēmas nosaukums brīvā tekstā	Name of the identification scheme, in a free text form
9.1.20		[0..1]	++++++Issuer	<Issr>	Max35Text		
9.1.21	Or}	[1..1]	+++++PrivatIdentification	<PrvtId>	Component	Privātpersonas Identifikators	Unique and unambiguous identification of a person, e.g. passport
9.1.22		[0..1]	++++++DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Component	SEPA	Informācija par dzimšanas vietu un laiku
9.1.23		[1..1]	++++++BirthDate	<BirthDt>	ISODate		ISODate
9.1.25		[1..1]	++++++CityOfBirth	<CityOfBirth>	Max35Text		
9.1.26		[1..1]	++++++CountryOfBirth	<CtryOfBirth>	CountryCode	Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2)

						code_elements.htm	code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.27		[0..n]	++++++Other	<Othr>	Component		
9.1.28		[1..1]	++++++Identification	<Id>	Max35Text	Privātpersonas personas kods	Private personal code
9.1.29		[0..1]	++++++SchemeName	<SchmeNm>	Choice Component		
9.1.30	{Or	[1..1]	++++++Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis lauks satur NIDN. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Name of the identification scheme, If personal code is used, NIDN is displayed Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.31	Or}	[1..1]	++++++Proprietary	<Prtry>	Max35Text	Identifikācijas shēmas nosaukums brīvā tekstā	Name of the identification scheme, in a free text form
9.1.32		[0..1]	++++++Issuer	<Issr>	Max35Text		
9.1.33		[0..1]	+++CountryOfResidence	<CtryOfRes>	CountryCode	Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
2.80 +		[1..1]	+++CreditorAccount	<CdtrAcct>	Cash Account Component	Informācija par maksājuma saņēmēja konta numuru (kreditejamais konts). OBLIGĀTI aizpildāms lauks	Beneficiary account Component is MANDATORY even if it is not required by scheme
1.1.0		[1..1]	+++Identification	<Id>	Account Identification Component		
1.1.1	{Or	[1..1]	++++IBAN	<IBAN>	IBANIdentifier	Kreditejamais konts IBAN formātā. Obligāts maksājumiem Latvijā un SEPA maksājumiem	IBAN
1.1.2	Or}	[1..1]	++++Other	<Othr>	Component		
1.1.3		[1..1]	++++++Identification	<Id>	Max34Text	Saņēmēja konts ne-IBAN formātā	BBAN (account other than IBAN if IBAN not available)
2.81 +		[0..1]	+++UltimateCreditor	<UltmCdtr>	Party Identification Component	Informācija par Galējo maksājuma saņēmēju <i>Piemērs:</i> Uzņēmums veic algas maksājumu vasaras darbiniekam (skolniekiem), kuram nav atvērts norēķinu konts. Maksājums tiek veikt par labu kādam no viņa vecākiem, šajā laikā norādot datus par skolnieku.	Ultimate party to which an amount of money is due. <i>Example:</i> Payment is made by a company to their temporary employee (e.g. student) who doesn't have an account. Payment is made to component.

9.1.0	[0..1]	++++Name	<Nm>	Max140Text		Galējā maksājuma saņēmēja nosaukums SEPA maksājuma gadījumā lauka garums starpbanku posmā ir ierobežots līdz 70 zīmēm. Ja tiks norādīts lielāks zīmu skaits, banka saglabās tikai pirmās 70 zīmes.	Name of Ultimate Creditor In case of SEPA payment length of the tag is limited to 70 characters. If longer value will be presented by customer, then only first 70 characters will be forwarded.
9.1.12	[0..1]	++++Identification	<Id>	Choice Component		Galējā maksājuma saņēmēja identifikators	Unique and unambiguous identification of a party
9.1.13	{Or} [1..1]	+++++OrganisationIdentification	<OrgId>	Component		Uzņēmuma identifikators	Unique and unambiguous way to identify an organisation
9.1.14	[0..1]	++++++BICOrBEI	<BICOrBEI>	Identifier			
9.1.15	[0..n]	++++++Other	<Othr>	Component			
9.1.16	[1..1]	++++++Identification	<Id>	Max35Text		Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or Tax Payer number
9.1.17	[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.18	[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts nodokļu maksātāja kods, šis laiks satur TXID. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	Name of the identification scheme, in a coded form as published in an external list. If Tax Payer number is used, TXID is displayed. Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.21	Or} [1..1]	+++++PrivatIdentification	<PrvtId>	Component		Privātpersonas identifikators	Unique and unambiguous identification of a person, e.g. passport
9.1.22	[0..1]	++++++DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Component		Informācija par dzimšanas vietu un laiku	Date and place of birth of a person
9.1.23	[1..1]	++++++BirthDate	<BirthDt>	ISODate			ISODate
9.1.25	[1..1]	++++++CityOfBirth	<CityOfBirth>	Max35Text			
9.1.26	[1..1]	++++++CountryOfBirth	<CtryOfBirth>	CountryCode		Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
9.1.27	[0..n]	+++++Other	<Othr>	Component			
9.1.28	[1..1]	++++++Identification	<Id>	Max35Text		Privātpersonas personas kods	Private personal code
9.1.29	[0..1]	++++++SchemeName	<SchmeNm>	Choice Component			
9.1.30	[1..1]	++++++Code	<Cd>	Code		Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis laiks satur	Name of the identification scheme, If personal code is used, NIDN is displayed

						NIDN. Pielāutie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Allowed codes are available http://www.iso20022.org/external_code_list.page in sheet ExternalOrganisationIdentification1Code
9.1.33	[0..1]	++++CountryOfResidence	<CtryOfRes>	CountryCode		Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
2.85	[0..1]	+++InstructionForDebtorAgent	<InstrForDbtrAgt>	Max140Text	Individuāli	Papildus rīkojums debitorbankai no maksātāja. (papildus informācija brīvā formātā).	Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent
2.86	[0..1]	+++Purpose	<Purp>	Choice component		Maksājuma mērķis kodētā veidā	Underlying reason for the payment transaction. <i>Usage:</i> Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain
2.87	[1..1]	++++Code	<Cd>	ExternalPurpose Code		Atbilstošais maksājuma mērķa ISO kods: http://www.iso20022.org/external_code_list.page sarakstā ExternalPurpose1Code	Underlying reason for the payment transaction, as published in an external purpose code list http://www.iso20022.org/external_code_list.page
2.89	[0..10]	+++RegulatoryReporting	<RgltryRptg>	Component		Informācija/Atskaites, kas izriet no normatīvajām un/vai likumu prasībām. Kā piemēram tiek izmantots AMK kodus ievadei, rubļu maksājumiem VO un KBK kodiem un līdzīgas informācijas norādīšanai.	Information needed due to regulatory and statutory requirements. Tag can be used to display AMK codes (Latvian specific); VO and KBK codes for Russian rouble payments.
11.1.1	[0..1]	++++Authority	<Authrty>	Component		Norāda uz informācijas saņēmēju (piemēram valsts, kura piepras konkrēto papildinformāciju par darījumu)	Entity requiring the regulatory reporting information
11.1.3	[0..1]	+++++Country	<Ctry>	CountryCode		Valsts kods (AMK gadījuma LV, Krievijas rubļu gadījumā RU u.t.t.). Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
11.1.4	[0..n]	++++Details	<Dtls>	Component		Precīza informācija par normatīvo prasību datiem	Set of elements used to provide details on the regulatory reporting information
11.1.5	[0..1]	+++++Type	<Tp>	Max35Text		Informācijas/atskaites tips. Piemēram, AMK	Specifies the type of the information supplied in the regulatory reporting details

						AMK - Ārējo maksājumu klasifikatora kods Latvijas gadījumā VO - Valūtas operāciju kods Krievijas gadījumā KBK – Budžeta klasifikācijas kods Krievijas gadījumā. u.c.	<i>Example:</i> AMK – external payment classification codes in Latvia; VO - Code of currency transaction for Russian rouble payments; KBK – budget classification codes for Russian rouble payments
11.1.7	[0..1]	+++++Country	<Ctry>	CountryCode		Kreditora rezidences valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code) http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm
11.1.8	[0..1]	+++++Code	<Cd>	Code		Precīzs informācijas/atskaites kods Piemēram: 111 - preču eksports imports (AMK kodu liste: http://www.bank.lv/tiesibu-akti/arejo-maksajumu-klasifikators-amk-21) Tāpat šeit vadāmi citi līdzīgi kodi.	Code AMK – 3 digits; VO – 5 digits etc.
11.1.9	[0..1]	+++++Amount	<Amt>	Amount		Atskaitē norādītā darījuma summa	Amount of money to be reported for regulatory and statutory requirements
11.1.10	[0..1]	+++++Information	<Inf>	Max35Text			
2.98	[0..1]	+++RemittanceInformation	<RmtInf>	Component		Bloks kurā tiek norādīta informācija saņēmējam (Maksājuma detaļas)	Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system
2.99	{Or [0..n]}	++++Unstructured	<Ustrd>	Max140Text	Individuāli	Informācija saņēmējam (Maksājuma detaļas/mērkis) brīvā formā max 140 simboli. Nav atļauts aizpildīt vienlaicīgi ar strukturēto informāciju saņēmējam (Lauks 2.100). Elementu atļauts lietot tikai vienu reizi katrā maksājumā, ja individuāli ar banku nav panākta cita vienošanās.	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form. Can not be filled if tag 2.100 is also present. It is only allowed to use the tag once in every payment, unless otherwise agreed with a bank
2.100	Or} [0..n]	++++Structured	<Strd>	Component		Informācija saņēmējam (Maksājuma detaļas/mērkis) Strukturētā formātā. Nav atļauts aizpildīt vienlaicīgi ar nestukturēto informāciju saņēmējam (Lauks 2.99). Elementu atļauts lietot tikai vienu reizi katrā maksājumā. Kopējais komponentē atspoguļotās informācijas garums nedrīkst pārsniegt 140 zīmes.	Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form. Can not be filled if tag 2.99 is also present. It is only allowed to use the tag once in every payment.

							Overall length of the component is max.140 symbols.
2.120	[0..1]	+++++CreditorReferenceInformation	<CdtrRefInf>	Component		Kreditora (saņēmēja) piešķirta reference, kas paredzēta maksājumam par pamatu esošā dokumenta identificēšanai. Aizpildot šo lauku, ir obligāti jāaizpilda arī atribūts 2.121 ar apakšatribūtiem (2.122 un 2.123).	Reference information provided by the creditor to allow the identification of the underlying documents. If this component is used then all the attributes (2.121; 2.122; 2.123) should be filled.
2.121	[0..1]	++++++Type	<Tp>	Component		Kreditora noteiktās references tips	Specifies the type of creditor reference
2.122	[1..1]	++++++CodeOrProprietary	<CdOrPrtry>	Component		Kreditora noteiktās references tips kodētā veidā	Coded or proprietary format creditor reference type
2.123	[1..1]	++++++Code	<Cd>	Code		Kreditora references tipa kods; izmantotais kods: SCOR - Dokuments ir strukturēts ziņojums	Type of creditor reference, in a coded form. SCOR - Document is a structured communication reference provided by the creditor to identify the referred transaction
2.125	[0..1]	++++++Issuer	<Issr>	Max35Text		Maksājuma references izsniedzējs	Entity that assigns the credit reference type
2.126	[0..1]	+++++Reference	<Ref>	Max35Text		Maksājuma references numurs	Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction

Specifiskas informācijas ievadīšana

AMK koda norādīšana

Lai maksājumā norādītu AMK kodu, nepieciešams aizpildīt sadaļu „RegulatoryReporting” (lauks 2.89) ar sekojošu informāciju:

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.89	[0..10]	+++RegulatoryReporting	<RgltryRptg>	Component		
11.1.1	[0..1]	++++Authority	<Authrty>	Component		
11.1.3	[0..1]	+++++Country	<Ctry>	CountryCode	Valsts kods - LV	Country code – LV
11.1.4	[0..n]	++++Details	<Dtls>	Component		
11.1.5	[0..1]	+++++Type	<Tp>	Max35Text	Koda tips - AMK	Code type – AMK
11.1.8	[0..1]	+++++Code	<Cd>	Code	Precīzs darījuma kods Piemēram: 111 - preču eksports imports	Exact code. Example: 111 – import/export of goods

XML paraugs:

```
<RgltryRptg>
  <Authrty>
    <Ctry>LV</Ctry>
  </Authrty>
  <Dtls>
    <Tp>AMK</Tp>
    <Cd>111</Cd>
  </Dtls>
</RgltryRptg>
```

Budžetu klasifikācijas kods (EKK)

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.89	[0..10]	+++RegulatoryReporting	<RgltryRptg>	Component		
11.1.1	[0..1]	++++Authority	<Authrty>	Component	Norāda uz informācijas saņēmēju (Piemēram, valsts kura pieprasī konkrēto papildinformāciju par darījumu)	Entity requiring the regulatory reporting information
11.1.3	[0..1]	+++++Country	<Ctry>	CountryCode	Valsts kods - LV	Country code – LV
11.1.4	[0..n]	+++++Details	<Dtls>	Component	Precīza informācija par normatīvo prasību datiem	Set of elements used to provide details on the regulatory reporting information
11.1.5	[0..1]	+++++Type	<Tp>	Max35Text	Koda tips - EKK	Specifies the type of the information supplied in the regulatory reporting details. Code type - EKK
11.1.8	[0..1]	+++++Code	<Cd>	Code	Kodu vērtības saskanā ar: MK noteikumi Nr.875 (22.11.2005.) "Noteikumi par budžetu finansēšanas klasifikāciju" MK noteikumi Nr.1031 (27.12.2005.) "Noteikumi par budžetu izdevumu klasifikāciju atbilstoši ekonomiskajām kategorijām" MK noteikumi Nr.1032 (27.12.2005.) "Noteikumi par budžetu ieņēmumu klasifikāciju"	Codes according to regulations of Cabinet of Ministers No. 875; No.1031; No.1032.
11.1.9	[0..1]	+++++Amount	<Amt>	Amount	Klasifikācijas kodam (lauks 11.1.8) atbilstošā darījuma summa un valūta	Amount of money to be reported for regulatory and statutory requirements and currency
11.1.10	[0..1]	+++++Information	<Inf>	Max35Text	Izmantojamās vērtības: DR – saņēmēja Code un Amount vērtības CR – maksātāja Code un Amount vērtības	Values to be used: DR – Code and Amount values of Payee CR – Code and Amount values of Payer

* Details sadalā, ja Amount ir EUR, maksimāli atlauts norādīt desmit Code blokus ar Information vērtību „DBIT” un desmit Code blokus ar Information vērtību „CRDT”. Ja Amount valūta nav EUR maksimāli atlauts norādīt vienu Code bloku

** Komercbankas apstrādā tikai vienu kodu kā norādīts 2-piemērā

1- piemērs (Valsts kases ietvaros)

```

<RgltryRptg>
  <Authrty>
    <Ctry>LV</Ctry>
    </Authrty>
  <Dtls>
    <Tp>EKK</Tp>
    <Cd>2231</Cd>
    <Amt Ccy="EUR">2</Amt>
    <Inf>DBIT</Inf>
  </Dtls>
  <Dtls>
    <Tp>EKK</Tp>
    <Cd>21499</Cd>
    <Amt Ccy="EUR">2</Amt>
    <Inf>CRDT</Inf>
  </Dtls>
</RgltryRptg>

```

2- piemērs (No komercbankām uz Valsts kasi)

```

<RgltryRptg>
  <Authrty>
    <Ctry>LV</Ctry>
    </Authrty>
  <Dtls>
    <Tp>EKK</Tp>
    <Cd>2231</Cd>
  </Dtls>
</RgltryRptg>

```

Rubļu maksājums uz Krieviju

Lai norādītu korekti maksājuma izpildei nepieciešamo informāciju, jāaizpilda zemāk minētās sadaļas:

Saņēmēja bankas kods – BIK

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.77 +	[0..1]	+++CreditorAgent	<CdtrAgt>	Financial Institution Identification Component	Informācija par saņēmēja banku (kreditorbanka)	Beneficiary bank information should be displayed
6.1.0	[1..1]	++++FinancialInstitutionIdentification	<FinInstnId>	Component	Finanšu institūcijas identifikācijas sadaļa	Identification of financial institution
6.1.2	[0..1]	+++++ClearingSystemMemberIdentification	<ClrSysMmbld>	Component		
6.1.3	[0..1]	++++++ClearingSystemIdentification	<ClrSysId>	Choice Component	Kliringa sistēmas identifikators	Clearing system identifier
6.1.4	[1..1]	++++++Code	<Cd>	Code	Konstants kods - RUCBC	Fixed value - RUCBC
6.1.6	[1..1]	++++++MemberIdentification	<Mmbld>	Max35Text	Saņēmēja bankas BIK koda vērtība	BIK code of beneficiary bank

*Šajā sadaļā tiek norādīts arī saņēmēja bankas nosaukums un adrese.

Saņēmēja bankas korespondējošais konts

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.78 +	[0..1]	+++CreditorAgentAccount	<CdtrAgtAcct>	Cash Account Component		
1.1.0		++++Identification	<Id>			
1.1.2		+++++Other	<Othr>			
1.1.3		++++++Identification	<Id>		Saņēmēj bankas korespondentkonts (konta numurs)	Correspondent account of beneficiary bank (account number in Central Bank)

Saņēmēja INN vai KIO kods

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.79 +	[1..1]	+++Creditor	<Cdtr>	Party Identification Component		
9.1.12	[0..1]	++++Identification	<Id>	Choice Component		
9.1.13	[1..1]	+++++OrganisationIdentification	<OrgId>	Component	Uzņēmuma identifikators	Organisation identification
9.1.15	[0..n]	++++++Other	<Othr>	Component		

9.1.16	[1..1]	+++++++Identification	<Id>	Max35Text	INN kods (piemēram INN1234567890); KIO ((КИО – Код иностранной организации) - ārzemju organizācijas kods).	INN code (e.g. INN1234567890); KIO code ((КИО – Код иностранной организации) – code of foreign organisation).
9.1.17	[0..1]	+++++++SchemeName	<SchmeNm>	Choice Component		
9.1.19	[1..1]	+++++++Proprietary	<Prtry>	Max35Text	Koda tips, konstante INN vai KIO	Code type – only INN or KIO should be present

Saņēmēja KPP kods

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.79 +	[1..1]	+++Creditor	<Cdtr>	Party Identification Component		
9.1.12	[0..1]	++++Identification	<Id>	Choice Component		
9.1.13	[1..1]	+++++OrganisationIdentification	<OrgId>	Component	Uzņēmuma identifikators	Organisation identifier
9.1.15	[0..n]	++++++Other	<Othr>	Component		
9.1.16	[1..1]	+++++++Identification	<Id>	Max35Text	KPP kods (piemēram KPP987654321)	KPP code (e.g. KPP987654321)
9.1.17	[0..1]	+++++++SchemeName	<SchmeNm>	Choice Component		
9.1.19	[1..1]	+++++++Proprietary	<Prtry>	Max35Text	Koda tips, konstante KPP	Code type – fixed value KPP

Valūtas operācijas kods (VO kods)

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.89	[0..10]	+++RegulatoryReporting	<RgltryRptg>	Component		
11.1.1	[0..1]	++++Authority	<Authrty>	Component	Norāda uz informācijas saņēmēju (Piemēram valsts institūcija, kura pieprasī konkrēto papildinformāciju par darījumu)	Indicates the receiver of this information (e.g. State institution that requests this information about transaction)
11.1.3	[0..1]	++++Country	<Ctry>	CountryCode	Valsts kods - RU	Country code – RU
11.1.4	[0..n]	++++Details	<Dtls>	Component	Precīza informācija par normatīvo prasību datiem	Precise information about required data
11.1.5	[0..1]	++++Type	<Tp>	Max35Text	Koda tips - VO	Code type – VO
11.1.10	[0..1]	++++Information	<Inf>	Max35Text	Valūtas operācijas kods (5 cipari)	Code value (5 digits)

Budžeta klasifikācijas kods (KBK kods)

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.89	[0..10]	+++RegulatoryReporting	<RgltryRptg>	Component		
11.1.1	[0..1]	++++Authority	<Authrty>	Component	Norāda uz informācijas saņēmēju (Piemēram, valsts kura pieprasī konkrēto papildinformāciju par darījumu)	Indicates the receiver of this information (e.g. State institution that requests this information about transaction)
11.1.3	[0..1]	+++++Country	<Ctry>	CountryCode	Valsts kods - RU	Country code – RU
11.1.4	[0..n]	+++++Details	<Dtls>	Component	Precīza informācija par normatīvo prasību datiem	Precise information about required data
11.1.5	[0..1]	++++++Type	<Tp>	Max35Text	Koda tips - KBK	Code type – KBK
11.1.10	[0..1]	++++++Information	<Infr>	Max35Text	KBK kods (vērtība)	Code value

* Authority sadaļa netiek dublēta, skaitāt piemēru maksājumu paraugu sadaļā.

Maksājumi uz citām valstīm, kas uztur noteiktus iekšzemes banku identifikatorus (piem. FW/ABA- ASV; Transit number- Kanāda)

Lai norādītu korekti maksājuma izpildei nepieciešamo informāciju, jāaizpilda zemāk minētās sadaļas:

Piemērs ar Fedwire Routing Number (American Bankers Association, ABA – 9 ciparu kods)

Ind.	Mult.	Ziņojuma elements	<XML Tags>	Tips	Komentāri par laukā ievadāmo informāciju	Comments about particular tag
2.77 +	[0..1]	+++CreditorAgent	<CdtrAgt>	Financial Institution Identification Component	Informācija par saņēmēja banku (kreditorbanka)	Beneficiary bank information should be displayed
6.1.0	[1..1]	++++FinancialInstitutionIdentification	<FinInstnId>	Component	Finanšu institūcijas identifikācijas sadaļa	Identification of financial institution
6.1.2	[0..1]	+++++ClearingSystemMemberIdentification	<ClrSysMmbld>	Component		
6.1.3	[0..1]	++++++ClearingSystemIdentification	<ClrSysId>	Choice Component	Klīringa sistēmas identifikators	Clearing system identifier
6.1.4	[1..1]	++++++Code	<Cd>	Code	Konstants kods - USABA	Fixed value - USABA
6.1.6	[1..1]	++++++MemberIdentification	<Mmbld>	Max35Text	Saņēmēja bankas ABA koda vērtība	ABA code of beneficiary bank (9 digits)

* Šajā sadaļā tiek norādīts arī saņēmēja bankas nosaukums un adrese.

Maksājumu paraugi

```
<?xml version="1.0" encoding="UTF-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.001.001.03" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" >
  <CstmrCdtTrfInitn>
    <GrpHdr>
      <MsgId>MSG25102012-01</MsgId>
      <!--Unikāls maksājuma identifikators-->
      <CreDtTm>2012-10-25T09:23:40</CreDtTm>
      <!--Ziņojuma izveides laiks-->
      <NbOfTx>3</NbOfTx>
      <!--Darījumu skaits failā-->
      <CtrlSum>13500</CtrlSum>
      <!--Kopējā darījumu summa-->
      <InitgPty>
        <!--Maksājumu ierosinōsā puse-->
        <Nm>Ierosinātājs AS</Nm>
        <!--Maksājumu ierosinošās puses nosaukums-->
        <Id>
          <OrgId>
            <Othr>
              <Id>900000000000</Id>
              <!--Maksājumu ierosinošās puses reģistrācijas numurs-->
            </Othr>
          </OrgId>
        </Id>
      </InitgPty>
    </GrpHdr>
    <PmtInf>
      <PmtInfld>PAY25102012-01</PmtInfld>
      <!--Unikāls maksājumu sekcijas identifikators-->
      <PmtMtd>TRF</PmtMtd>
      <!--Ziņojumā ieklauto darījumu tips, tiek izmantots tikai kods TRF - maksājumi-->
      <NbOfTx>3</NbOfTx>
      <!--Darījumu skaits maksājumu sekcijā-->
      <CtrlSum>13500</CtrlSum>
      <!--Kopējā darījumu summa maksājumu sekcijā-->
      <ReqdExctnDt>2012-10-25</ReqdExctnDt>
      <!--Datums kurā maksājums jāizpilda-->
      <Dbtr>
        <!--Informācija par maksātāju-->
```

```

<Nm>Uzņēmums SIA</Nm>
<!--Maksātāja nosaukums/vārds-->
<Id>
  <OrgId>
    <Othr>
      <Id>900000000001</Id>
      <!--Maksātāja reģistrācijas numurs-->
      <SchmeNm>
        <Cd>TXID</Cd>
        <!--Kods norāda uz ID lauka ievadīto vērtību (nodokļu maksātāja kods).-->
      </SchmeNm>
    </Othr>
  </OrgId>
</Id>
</Dbtr>
<DbtrAcct>
  <Id>
    <IBAN>LV00TEST00000000000001</IBAN>
    <!--Maksātāja konts no kura tiks veikti zemāk norādītie darījumi -->
  </Id>
</DbtrAcct>
<DbtrAgt>
  <FinInstnId>
    <BIC>TESTLV22</BIC>
    <!--Maksātāja bankas identifikators (BIC)-->
  </FinInstnId>
</DbtrAgt>
<CdtTrfTxInf>
  <!--EUR maksājums starp divām Latvijas bankām (starp diviem rezidentiem)-->
  <PmtId>
    <InstrId>PAY25102012-01/1</InstrId>
    <!--Unikāls maksājuma identifikators (maksājuma numurs)-->
    <EndToEndId>PAY-01/1</EndToEndId>
    <!--End to End Id Tieka izmantots tikai SEPA maksājumā, šeit tiks ignorēts-->
  </PmtId>
  <PmtTpInf>
    <LclInstrm>
      <Prtry>NORM</Prtry>
      <!--Maksājuma izpildes prioritāte-->
    </LclInstrm>
    <CtgyPurp>
      <Cd>SUPP</Cd>
      <!--Maksājuma tipa kods(maksājums piegādātājam)-->
    </CtgyPurp>
  </PmtTpInf>
</CdtTrfTxInf>

```

```

        </CtgyPurp>
</PmtTpInf>
<Amt>
    <InstdAmt Ccy="EUR">1000</InstdAmt>
    <!--Maksājuma summa un valūta-->
</Amt>
<ChrgBr>SLEV</ChrgBr>
<!--Komisijas tips. EEZ maksājumiem tikai SLEV -->
<CdtrAgt>
    <!--Informācija par saņēmēja banku-->
    <FinInstnId>
        <BIC>TESSLV20</BIC>
        <!--Saņēmēja bankas identifikators (BIC)-->
        <Nm>SaņēmejBANKA</Nm>
        <!--Saņēmēja bankas nosaukums-->
    </FinInstnId>
</CdtrAgt>
<Cdtr>
    <!--Informācija par maksājuma saņēmēju-->
    <Nm>Saņēmējs SIA</Nm>
    <!--Saņēmēja nosaukums-->
    <PstlAdr>
        <!--Pasta adrese-->
        <Ctry>LV</Ctry>
        <AdrLine>Rīga, Brīvības iela 1, LV- 1010</AdrLine>
    </PstlAdr>
    <Id>
        <OrgId>
            <Othr>
                <Id>900000000002</Id>
                <!--Saņēmēja reģistrācijas numurs-->
                <SchmeNm>
                    <Cd>TXID</Cd>
                    <!--Kods norāda uz ID laukā ievadītas informācijas formu -->
                </SchmeNm>
            </Othr>
        <OrgId>
    </Id>
    <CtryOfRes>LV</CtryOfRes>
    <!--Saņēmēja rezidences valsts-->
</Cdtr>
<CdtrAcct>
    <Id>

```

```

<IBAN>LV00TESS00000000000002</IBAN>
<!--Saņēmēja konta numurs-->
</Id>
</CdtrAcct>
<RmtInf>
  <Ustrd>Maksājums par precēm</Ustrd>
  <!--Informācija saņēmējam, brīvā formā (maksājuma detaļas)-->
</RmtInf>
</CdtTrfTxInf>
<CdtTrfTxInf>
  <!--EUR Maksājums no bankas Latvijā uz banku Vācijā-->
<PmtId>
  <InstrId>PAY25102012-01/2</InstrId>
  <EndToEndId>PAY-01/2</EndToEndId>
</PmtId>
<PmtTpInf>
  <LclInstrm>
    <Prtry>NORM</Prtry>
  </LclInstrm>
  <CtgyPurp>
    <Cd>SUPP</Cd>
  </CtgyPurp>
</PmtTpInf>
<Amt>
  <InstdAmt Ccy="EUR">2500</InstdAmt>
  <!--Maskājuma summa un valūta -->
</Amt>
<ChrgBr>SLEV</ChrgBr>
<!--Komisijas tips. EEZ maksājumiem tikai SLEV-->
<CdtrAgt>
  <FinInstnId>
    <BIC>GERMDEFF</BIC>
    <Nm>Vācijas SaņēmējBANK</Nm>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>Saņēmējs Vācijā</Nm>
  <!--Saņēmēja nosaukums-->
<PstlAdr>
  <Ctry>DE</Ctry>
  <AdrLine>Taunusanlage 12, 60325, Frankfurt am Main</AdrLine>
</PstlAdr>
<CtryOfRes>DE</CtryOfRes>

```

```

</Cdtr>
<CdtrAcct>
  <Id>
    <IBAN>DE000000000000000000000000000001</IBAN>
    <!--Saņēmēja konta numurs. SEPA maksājumime tikai IBAN-->
  </Id>
</CdtrAcct>
<RgltryRptg>
  <!--Normatīvos aktos parēdzētās atskaites par maksājumu-->
  <Authrty>
    <Ctry>LV</Ctry>
    <!--Valsts kurai atskaitē tiek sniepta-->
  </Authrty>
  <DtIs>
    <Tp>AMK</Tp>
    <!--Atskaites tips (šajā gadījumā AMK kods)-->
    <Cd>111</Cd>
    <!--Precīza vērtība-->
  </DtIs>
</RgltryRptg>
<RmtlInf>
  <!--Saņēmēja informācijas bloks, NAV ATĻAUTS LIETOT VIENLAICĪGI Ustrd UN Strd BLOKUS-->
  <Strd>
    <!--Structurēta Informācija Saņēmējam-->
    <CdtrRefInf>
      <Tp>
        <CdOrPrtry>
          <Cd>SCOR</Cd>
        </CdOrPrtry>
      </Tp>
      <Ref>ORDER20121101</Ref>
    </CdtrRefInf>
  </Strd>
</RmtlInf>
</CdtTrfTxlnf>
<CdtTrfTxlnf>
  <!--Krievijas rubļu maksājums no bankas Latvija uz banku Kreivijā-->
  <PmtId>
    <InstrId>PAY25102012-01/3</InstrId>
    <EndToEndId>PAY-01/3</EndToEndId>
  </PmtId>
  <PmtTpInf>
    <LclInstrm>

```

```
    <Prtry>HIGH</Prtry>
  </LclInstrm>
  <CtgyPurp>
    <Cd>SUPP</Cd>
  </CtgyPurp>
</PmtTpInf>
<Amt>
  <InstdAmt Ccy="RUB">10000</InstdAmt>
  <!--Maksājuma summa un valūta-->
</Amt>
<ChrgBr>DEBT</ChrgBr>
<CdtrAgt>
  <FinInstnId>
    <ClrSysMmbld>
      <ClrSysId>
        <Cd>RUCBC</Cd>
      </ClrSysId>
      <Mmbld>044030755</Mmbld>
    </ClrSysMmbld>
    <Nm>OAO BANK ALEKSANDROVSKI</Nm>
    <PstlAdr>
      <Ctry>RU</Ctry>
    </PstlAdr>
  </FinInstnId>
</CdtrAgt>
<CdtrAgtAcct>
<Id>
  <Othr>
    <Id>3010181000000000755</Id>
  </Othr>
</Id>
</CdtrAgtAcct>
<Cdtr>
  <Nm>OAO CREDITOR</Nm>
  <!--Creditor name-->
  <PstlAdr>
    <Ctry>RU</Ctry>
  </PstlAdr>
<Id>
  <OrgId>
    <Othr>
      <Id>INN7804216912</Id>
    <SchmeNm>
```

```
    <Prtry>INN</Prtry>
    </SchmeNm>
    </Othr>
    <Othr>
        <Id>KPP780201001</Id>
        <SchmeNm>
            <Prtry>KPP</Prtry>
        </SchmeNm>
    </Othr>
    </OrgId>
</Id>
</Cdtr>
<CdtrAcct>
    <Id>
        <Othr>
            <Id>40702812345678978901</Id>
            <!--Konts kurā tiks ieskaitīti naudas līdzekļi-->
        </Othr>
    </Id>
</CdtrAcct>
<RgltryRptg>
    <Authrty>
        <Ctry>LV</Ctry>
    </Authrty>
    <Dtls>
        <Tp>AMK</Tp>
        <Cd>111</Cd>
    </Dtls>
</RgltryRptg>
<RgltryRptg>
    <Authrty>
        <Ctry>RU</Ctry>
    </Authrty>
    <Dtls>
        <Tp>VO</Tp>
        <Inf>13010</Inf>
    </Dtls>
    <Dtls>
        <Tp>KBK</Tp>
        <Inf>31810805000110111110</Inf>
    </Dtls>
</RgltryRptg>
<RmtInf>
```

```
<Ustrd>SCET 12345</Ustrd>
</RmtInf>
</CdtTrfTxInft>
</PmtInft>
</CstmrCdtTrfInitn>
</Document>
```

2. Maksājumu statusa atbildes ziņojums

pain.002.001.03

Dokumenta mērķis ir sniegt vadlīnijas ISO20022 XML – pain.002.001.03 maksājuma statusa ziņojumu izveidei, kuru no bankas saņems klients, atsūtot bankai maksājuma iniciēšanas dokumentu (pain.001.001.03).

Maksājuma statusa ziņojumu satura apraksts

Ziņojums satur divus obligātos blokus: Galvene (Header) un Informācija par oriģinālo maksājumu uzdevumu failu.

Galvene (Header):: Šis bloks tiek norādīts tikai vienu reizi un satur faila identificējošus elementus – Maksājuma Identifikators, ziņojuma izveides datums un laiks , maksājuma iniciējošā puse.

Informācija par oriģinālo maksājumu uzdevumu failu: No klienta saņemta failā var būt norādīts viens (vai vairāki) maksājumu bloki, un klients saņem attiecīgo struktūru maksājuma statuss reporta dokumentam.

Zemāk parādītajā tabulā aprakstīti ziņojumos izmantotie lauki sekojošā formātā:

Ind.	Or.	Mult.	Ziņojuma elements	<XML tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
		[1..1]	+ Message root				

Ind. – Ziņojuma elementa numurs. Numurs atbilst ISO 20022 XML Ziņojumu aprakstam, kurš ir atrodams vietnē www.iso20022.org zem “Catalogue of ISO 20022 messages” ar atsauci “pain.001.001.03”.

Or. – Norāda uz izvēlni. Ziņojumā var tikt iekļauts viens vai otrs elements.

Mult. – Norāda uz elementa izmantošanas obligātumu un šī elementa parādīšanās biežumu. Iespējamās vērtības un to nozīme:

- [1..1] – Elements ir obligāts un var tikt norādīts vienu reizi;
- [1..n] - Elements ir obligāts un var tikt norādīts vienu vai vairākas reizes;
- [0..1] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts tikai vienu reizi;
- [0..n] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts vienu vai vairākas reizes.

Ziņojuma elements – Elementa nosaukums atbilstoši ISO 20022 XML

XML tags – Atbilstošā elementa XML tags ziņojumā

Tips – XML tagā ievadītās informācijas apraksts

Lietojums – Papildus piezīmes par lauka lietošanu. Ja šī piezīme ir augstāka līmenē laukam, tā attiecās arī uz visiem šī lauka apakšlaukiem.

- Individuāli – Banka nenoraida maksājumu, taču laukā ievadīto informāciju izmanto pēc saviem ieskatiem vai saskaņā ar iepriekš panāktu vienošanos ar klientu.
- SEPA – Laiks tiek izmantots tikai SEPA maksājumiem

Komentāri – Papildus komentāri par lauka aizpildīšanu.

Ziņojuma elementi

Galvene – Header

Ind	Mult.	Ziņojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
1.0	[1..1]	+ Group Header	GrpHdr	Component		Ziņojuma informācija
1.1	[1..1]	++ Message Identification	MsgId	Max35Text		Unikāls ziņojuma identifikators, ko piešķir ziņojuma radītājs.
1.2	[1..1]	++ Creation Date Time	CreDtTm	ISODateTime		Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss Piemēram: 2012-11-21T09:10:49)
1.3	1..1]	++InitiatingParty	InitgPty	Component		Finanšu institūcija kurai pieder debetējamais konts (Banka kura veiks maksājumu)
9.1.12	[1..1]	+++Identification	Id	Component		
9.1.13	[1..1]	++++OrganisationIdentification	OrgId	Component		
9.1.14	[1..1]	+++++BICOrBEI	BICOrBEI	Identifier		Bankas BIC kods

Informācija par oriģinālo maksājumu uzdevumu failu

Ind	Mult.	Ziņojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
2	[1..1]	+ Original Group Information And Status	OrgnlGrpInfAndSts	Component		Informācija par maksājuma iniciēšanas ziņojumu
2.1	[1..1]	++ Original Message Identification	OrgnlMsgId	Max35Text		Maksājuma uzdevuma ziņojuma identifikators
2.2	[1..1]	++ Original Message Name Identification	OrgnlMsgNmId	Max35Text		Maksājuma uzdevuma ziņojuma shēmas identifikators
2.3	[0..1]	++ Original Creation Date Time	OrgnlCreDtTm	ISODateTime	Individuāli	Maksājuma uzdevuma ziņojuma izveidošanas laiks un datums
2.4	[0..1]	++ Original Number Of Transaction	OrgnlNbOfTxs	Max15NumericText	Individuāli	Maksājuma uzdevuma ziņojuma transakciju skaits
2.5	[0..1]	++ OriginalControlSum	OrgnlCtrlSum	DecimalNumber	Individuāli	Maksājuma uzdevuma ziņojuma transakciju kopsumma neskatoties uz valūtām
2.6	[0..1]	++ Group Status	GrpSts	TransactionGroupStatus3Code	Individuāli	Statuss par visām transakcijām
2.7	[0..n]	++ Status Reason Information	StsRsnInf	Component	Individuāli	Informācija par visu transakciju izpildes statusu Jābūt norādītam ‘Original Group Information and Status’, ‘Original Payment Information and Status’ vai ‘Transaction Information and Status’ līmenī.
2.8	[1..1]	+++Originator	Orgtr	Component		Jānorāda obligāti tikai, ja maksājums ir noraidīts
9.1.12	[0..1]	++++ Identification	Id	Component		
9.1.13	[1..1]	+++++ Organisation Identification	OrgId	Component		
9.1.14	[1..1]	++++++ BIC or BEI	BICOrBEI	AnyBICIdentifier		
2.9	[0..1]	+++ Reason	Rsn	Component		Transakcijas statusa iemesla kods

2.10	[1..1]	++++ Code	Cd	ExternalStatusReason1Code		For status reason code see External Code Lists spreadsheet
2.12	[0..n]	+++ Additional Information	AddtlInf	Max105Text		Tekstuāla informācija par izpildes statusu. Obligāti jāaizpilda ja iemesla kods (2.10) vienāds ar NARR
2.13	[0..n]	++ NumberOfTransactionsPerStatus	TxInfAndSts	Component	Individuāli	
2.14	[1..1]	+++ DetailedNumberOfTransactions	DtlNbOfTxs	Max15NumericText		
2.15	[1..1]	+++ DetailedStatuss	DtlSts	TransactionIndividualStatus3Code		

Maksājuma paciņas informācija

Ind	Mult.	Zinojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
3.0	[0..n]	+ Original Payment Information And Status	OrgnlPmtInfAndSts	Component		Informācija par maksājuma iniciēšanas paciņu
3.1	[1..1]	++ Original Payment Information Identification	OrgnlPmtInfd	Max35Text		Oriģināls maksājuma paciņas identifikators
3.2	[0..1]	++ Original Number of Transactions	OrgnlNbOfTxs	Max15NumericText	Individuāli	Maksājuma uzdevuma paciņas transakciju skaits
3.4	[0..1]	++ Payment Information Status	PmtInfSts	TransactionGroupStatus3Code	Individuāli	Statuss uz visām transakcijām paciņā
3.5	[0..n]	++ Status Reason Information	StsRsnInf	Component	Individuāli	Informācija par izpildes statusu transakcijām paciņā Jābūt norādītam ‘Original Group Information and Status’, ‘Original Payment Information and Status’ vai ‘Transaction Information and Status’ līmenī.
3.6	[1..1]	+++Originator	Orgtr	Component		Jānorāda obligāti tikai, ja maksājums ir noraidīts
9.1.12	[0..1]	++++ Identification	Id	Component		
9.1.13	[1..1]	+++++ Organisation Identification	Orgld	Component		
9.1.14	[1..1]	++++++ BIC or BEI	BICOrBEI	AnyBICIdentifier		
3.7	[0..1]	+++ Reason	Rsn	Component		Statusa iemesla kods
3.8	[1..1]	++++ Code	Cd	ExternalStatusReason1Code		For status reason code see External Code Lists spreadsheet
3.10	[0..n]	+++ Additional Information	AddtlInf	Max105Text		Tekstuāla informācija par izpildes statusu. Obligāti jāaizpilda ja iemesla kods (3.8) vienāds ar NARR

Transakcijas informācija

Ind	Mult.	Zinojuma elements	<XML Tags>	Tips	Lietojums	Komentāri par laukā ievadāmo informāciju
3.15	[0..n]	++ Transaction Information And Status	TxInfAndSts	Component		Informācija par maksājuma iniciēšanas transakciju
3.17	[0..1]	+++ Original Instruction Identification	OrgnlInstrId	Max35Text		Oriģināls transakcijas identifikators
3.18	[0..1]	+++ Original End to End Identification	OrgnlEndToEndId	Max35Text	SEPA	Oriģināls transakcijas end-to-end identifikators
3.19	[0..1]	+++ Transaction Status	TxSts	TransactionIndividualStatus3Code		Transakcijas izpildes statuss
3.20	[0..n]	+++ Status Reason Information	StsRsnInf	Component		Informācija par transakcijas izpildes statusu Jābūt norādītam ‘Original Group Information and Status’, ‘Original Payment Information and Status’ vai ‘Transaction Information and Status’ līmenī.
3.21	[1..1]	++++Originator	Orgtr	Component	Individuāli	Jānorāda obligāti tikai, ja maksājums ir noraidīts
9.1.12	[0..1]	+++++ Identification	Id	Component		
9.1.13	[1..1]	++++++ Organisation Identification	OrgId	Component		
9.1.14	[1..1]	++++++ BIC or BEI	BICOrBEI	AnyBICIdentifier		
3.22	[0..1]	++++ Reason	Rsn	Component		Transakcijas statusa iemesla kods
3.23	[1..1]	+++++ Code	Cd	ExternalStatusReason1Code		For status reason code see http://www.iso20022.org/External_Code_Lists_and_DSS.page External Code Lists spreadsheet
3.25	[0..n]	++++ Additional Information	AddtlInf	Max105Text		Tekstuāla informācija par transakcijas izpildes statusu. Obligāti jāaizpilda ja iemesla kods (3.23) vienāds ar NARR
3.32	[0..1]	+++ Original Transaction Reference	OrgnlTxRef	Component	Individuāli	Informācija papildus identificēšanai konkrētai transakcijai
3.34	[0..1]	++++Amount	Amt	Component		
3.35	[1..1]	+++++InstructedAmount	InstdAmt Ccy="AAA"	Amount		
3.41	[1..1]	++++RequestedExecutionDate	ReqdExctnDt	DateTime		
3.121	[1..1]	++++Debtor	Dbtr	Component		
9.1.0	[1..1]	+++++Name	Nm	Text		
3.122	[1..1]	++++DebtorAccount	<DbtrAcct>			
1.1.0	[1..1]	+++++Identification	<Id>			
1.1.1	[1..1]	++++++IBAN	<IBAN>	Identifier		
1.1.11	[1..1]	++++++Currency	<Ccy>	Code		
3.123	[1..1]	++++DebtorAgent	<DbtrAgt>			
6.1.0	[1..1]	+++++FinancialInstitutionIdentification	<FinInstnId>			
6.1.1	[1..1]	++++++BIC	<BIC>	Identifier		
3.125	[0..1]	++++CreditorAgent	<CdtrAgt>			

6.1.0	[1..1]	+++++FinancialInstitutionIdentification	<FinInstnId>			
6.1.1	[1..1]	++++++BIC	<BIC>	Identifier		
6.1.2	[1..1]	++++++ClearingSystemMemberIdentification	<ClrSysMmbld>			
6.1.3	[0..1]	++++++ClearingSystemIdentification	<ClrSysId>			
6.1.4	[1..1]	++++++Code	<Cd>	Code		
6.1.6	[1..1]	++++++MemberIdentification	<Mmbld>	Text		
3.127	[1..1]	++++Creditor	<Cdtr>			
9.1.0	[1..1]	++++Name	<Nm>	Text		
3.128	[1..1]	+++CreditorAccount	<CdtrAcct>			
1.1.0	[1..1]	++++Identification	<Id>			
1.1.1	[1..1]	++++++IBAN	<IBAN>	Identifier		
1.1.2	[1..1]	++++++Other	<Othr>			
1.1.3	[1..1]	++++++Identification	<Id>	Text		

Maksājumu statusa paraugs

Maksājuma statusa paraugs satur 3 dažādus maksājumu statusus:

1. EUR pārvedums starp divām Latvijas bankām;
2. EUR pārvedums no Latvijas uz Vāciju (SEPA maksājums);
3. Rubļu pārvedums no bankas Latvijā uz banku Krievijā.

```
<?xml version="1.0" encoding="UTF-8"?>
<Document xmlns="urn:iso:std:iso:20022:tech:xsd:pain.002.001.03" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <CstmrPmtStsRpt>
        <GrpHdr>
            <!-- Informācija par šo failu ar maksājumu statusiem -->
            <MsgId>STSRPTMSG25102012-41</MsgId>
            <!-- Unikāls faila identifikātors -->
            <CreDtTm>2012-10-25T09:23:42</CreDtTm>
            <!-- Šī faila ģenerēšanas datums un laiks -->
            <InitgPty>
                <Id>
                    <OrgId>
                        <BICOrBEI>TESTLV22</BICOrBEI>
                        <!-- Maksātāja banka -->
                    </OrgId>
                </Id>
            </InitgPty>
        </GrpHdr>
        <OrgnlGrpInfAndSts>
            <!-- Informācija par iriģinālo failu ar maksājumu uzdevumiem -->
            <OrgnlMsgId>MSG25102012-01</OrgnlMsgId>
            <!-- Maksājuma uzdevuma faila identifikātors -->
            <!-- Datu avots: CstmrCdtTrfInitn.GrpHdr.MsgId -->
            <OrgnlMsgNmId>pain.001.001.03</OrgnlMsgNmId>
            <!-- Maksājuma uzdevuma shēmas nosaukums -->
            <!-- Datu avots: konstante -->
            <OrgnlCreDtTm>2012-10-25T09:23:40</OrgnlCreDtTm>
            <!-- Maksājuma uzdevuma faila ģenerēšanas datums un laiks -->
            <!-- Datu avots: CstmrCdtTrfInitn.GrpHdr.CreDtTm -->
            <OrgnlNbOfTxns>3</OrgnlNbOfTxns>
            <!-- Lietotāja reportēts transakciju kopīgs skaits failā -->
            <!-- Datu avots: CstmrCdtTrfInitn.GrpHdr.NbOfTxns -->
        </OrgnlGrpInfAndSts>
        <OrgnlPmtInfAndSts>
```

```

<OrgnPmtInflId>PAY25102012-01</OrgnPmtInflId>
<!-- Maksājuma uzdevuma paciņas identifikātors -->
<!-- Datu avots: CstmrCdtTrfInitn.PmtInf.PmtInflId -->
<TxInflAndSts>
    <!-- Konkrēta transakcija -->
    <OrgnlnstrId>PAY25102012-01/1</OrgnlnstrId>
    <!-- Maksājuma uzdevuma identifikātors -->
    <!-- Datu avots: CstmrCdtTrfInitn.PmtInf.CdtTrfTxInfl.PmtId.InstrId -->
    <OrgnLEndToEndId>PAY-01/1</OrgnLEndToEndId>
    <!-- Maksājuma uzdevuma end-to-end identifikātors -->
    <!-- Datu avots: CstmrCdtTrfInitn.PmtInf.CdtTrfTxInfl.PmtId.EndToEndId -->
    <TxSts>RJCT</TxSts>
    <!-- Konkrētas transakcijas statuss -->
    <StsRsnInfl>
        <Orgtr>
            <Id>
                <OrgId>
                    <BICOrBEI>TESTLV22</BICOrBEI>
                </OrgId>
            </Id>
        </Orgtr>
        <Rsn>
            <Cd>AM04</Cd>
            <!-- Transakcijas statusa paskaidrojums -->
        </Rsn>
    </StsRsnInfl>
</TxInflAndSts>
<TxInflAndSts>
    <OrgnlnstrId>PAY25102012-01/2</OrgnlnstrId>
    <OrgnLEndToEndId>PAY-01/2</OrgnLEndToEndId>
    <TxSts>ACCP</TxSts>
</TxInflAndSts>
<TxInflAndSts>
    <OrgnlnstrId>PAY25102012-01/3</OrgnlnstrId>
    <!-- End-to-end id nav, jo nav sepa maksājums -->
    <TxSts>RJCT</TxSts>
    <StsRsnInfl>
        <Orgtr>
            <Id>
                <OrgId>
                    <BICOrBEI>TESTLV22</BICOrBEI>
                </OrgId>
            </Id>
        </Orgtr>

```

```
</Orgtr>
<Rsn>
    <Cd>NARR</Cd>
</Rsn>
<AddtlInf>Nepareizi norādīts KPP kods</AddtlInf>
<!-- Papildus informācija atteikumam -->
</StsRsnInf>
</TxInfAndSts>
</OrgnlPmtInfAndSts>
</CstmrPmtStsRpt>
</Document>
```

3. Konta pārskata ziņojums camt.052.001.02

Konta pārskata ziņojuma satura apraksts

Konta pārskata ziņojumu nosūta konto uzturētājs (kredītiestāde) konta īpašniekam vai tā pilnvarotai pusei. Šo ziņojumu izmanto, lai informētu konta īpašnieku, vai tā pilnvarotās personas par konta ierakstiem un/vai par konta bilanci konkrētā brīdī.

Konta pārskata ziņojums var saturēt informāciju par vairāk nekā vienu kontu. Tas sniedz informāciju, kas nepieciešama naudas plūsmas pārvaldībai un/vai bankas ierakstu saskaņošanu ar klienta datiem. Konta pārskatā iespējams atspoguļot:

- gaidāmos un iegrāmatotos darījumus;
- informāciju par konta bilanci.

Pārskatā var tikt ieklauta papildu detalizēta informācija par tajā atspoguļotajiem ierakstiem. Konta pārskatu var saņemt arī persona, kas nav konta īpašnieks, taču tai ir konta īpašnieka pilnvara konta informācijas saņemšanai.

Konta izraksta atspoguļošanai ir jāizmanto konta izraksta ziņojums.

Ziņojums satur divus obligātos blokus: Galvene (Header) un Pārskats (Account Report)

Galvene (Header): Šis bloks ir obligāts un tiek norādīts tikai vienu reizi. Tas satur faila identificējošus elementus – ziņojuma identifikators, ziņojuma izveides datums un laiks.

Konta pārskats (Account Report): Šis bloks ir obligāts un var tikt norādīts arī atkārtoti. Tas ir norādāms atkārtoti par katru pārskatā atspoguļoto kontu. Pārskats satur komponentes Bilance un Ieraksts.

Zemāk parādītajā tabula aprakstīti ziņojumos izmantotie lauki sekojošā formātā:

ISO Index	Or	Mult.	Ziņojuma elements	XML Tag	Tips	Komentāri par laukā ievadāmo informāciju (LAT/ENG)
		[1..1]	Message root	<BkToCstmrAcctRpt>		

Ind. – Ziņojuma elementa numurs. Numurs atbilst ISO 20022 XML Ziņojumu aprakstam, kurš ir atrodams vietnē http://www.iso20022.org/message_archive.page#first_version_bam zem "Second version of the Bank-to-Customer Cash Management messages" ar atsauci "camt.052.001.02".

Or. – Norāda uz izvēlni. Ziņojumā var tikt iekļauts viens vai otrs elements.

Mult. – Norāda uz elementa izmantošanas obligātumu un šī elementa parādīšanās biežumu. Iespējamās vērtības un to nozīme:

- [1..1] – Elements ir obligāts un var tikt norādīts vienu reizi;
- [1..n] - Elements ir obligāts un var tikt norādīts vienu vai vairākas reizes;
- [0..1] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts tikai vienu reizi;
- [0..n] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts vienu vai vairākas reizes.

Ziņojuma elements – Elementa nosaukums atbilstoši ISO 20022 XML

XML Tag – Atbilstošā elementa XML tags ziņojumā

Tips – XML tagā ievadītās informācijas apraksts

Komentāri – Papildus komentāri par lauka aizpildīšanu.

Piezīme: Bankas, atsevišķi vienojoties ar klientiem, var izmantot camt.060.001.03 ziņojumu, lai strukturētā veidā pieprasītu konta pārskatu. Piemēru skatīt zemāk

Index	Or	Mult.	Ziņojuma elements (Message Item)	XML Tag	Tips (Type)	Komentāri par laukā ievadāmo informāciju [LAT]	Comments about the tag
1.0		[1..1]	GroupHeader	<GrpHdr>			
1.1		[1..1]	Messageldeidentification	<MsgId>	Text	Reference, kuru piešķir kontu apkalpojošā institūcija un, kas tiek nosūtīta konta īpašniekam vai pilnvarotai personai, un, kam ir nepārprotami jāidentificē ziņojums. <i>Usage:</i> The account servicing institution has to make sure that Messageldeidentification is unique per account owner for a pre-agreed period.	Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message.
1.2		[1..1]	CreationDateTime	<CreDtTm>	DateTime	Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss, piemēram: 2012-11-21T09:10:49)	Date and time at which the message was created (DDDD-MM-DDThh:mm:ss, example: 2012-11-21T09:10:49).
1.3		[0..1]	MessageRecipient	<MsgRcpt>	+	Jānorāda, ja ziņojuma sanēmējs ir konta īpašnieka pilnvarotā puse. <i>Piezīme:</i> Izmantojam tikai gadījumā, ja izraksta sanēmējs nav konta īpašnieks	Party authorised by the account owner to receive information about movements on the account. <i>Usage:</i> MessageRecipient should only be identified when different from the account owner
9.1.0		[0..1]	Name	<Nm>	Text	Vārds/nosaukums vai cita informācija, kas neapšaubāmi identificē maksājuma iniciatoru.	Name by which a party is known and which is usually used to identify that party.
9.1.12		[0..1]	Identification	<Id>			
9.1.13		[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).

9.1.15	[0..n]	Other	<Othr>			
9.1.16	[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17	[0..1]	SchemeName	<SchmeNm>			
9.1.18	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis laiks satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	Codes can be found at http://www.iso20022.org/external_code_list.page in worksheet ExternalOrganisationIdentification1Code
1.4	[0..1]	MessagePagination	<MsgPgtn>	+	Lauks var noderēt ja tiek ģenerēts izraksts par lielu skaitu darījumu konkrētā periodā, un sistēma, caur kuru izraksts tiek ģenerēts, nespēj apstrādāt tik lielu ierakstu apjomu (piemēram 30K rindīnu izraksts, kamēr sistēma maksimāli spēj apstrādāt tikai 10K). Aktuāli lielajiem klientiem.	<p>Set of elements used to provide details on the page number of the message.</p> <p>Usage: The pagination of the message is only allowed when agreed between the parties.</p>
8.1.0	[1..1]	PageNumber	<PgNb>	Text		Page number
8.1.1	[1..1]	LastPageIndicator	<LastPgInd>	Indicator	Identificē pēdējo lapu (Yes/No)	Indicates the last page
2.0	[1..n]	Report	<Rpt>		Tiks atkārtots katrai valūtai, ja ziņojumā iekļauta informācija par multivalūtu kontu.	Will be repeated for each currency in case of multicurrency account
2.1	[1..1]	Identification	<Id>	Text	Unikāls ziņojuma identifikators, ko piešķir konta turētājs (kredītiestāde)	Unique identification, as assigned by the account servicer, to unambiguously identify the account statement
2.2	[0..1]	ElectronicSequenceNumber	<ElctrncSeqNb>	Quantity	Pārskata/izraksta kārtas skaitlis, kas pieaug ar katru nākamo pārskatu/izrakstu.	<p>Sequential number of the statement, as assigned by the account servicer.</p> <p>Usage: The sequential number is increased incrementally for each statement sent electronically.</p>

2.4	[1..1]	CreationDateTime	<CreDtTm>	DateTime	Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss, piemēram: 2012-11-21T09:10:49)	Date and time at which the message was created.
2.5	[0..1]	FromToDate	<FrToDt>	+	Laiks ir grāmatvedības 'noslēgšanas' laiks. Lietojams, ja ir nepieciešams norādīt konta pārskata sākumu un beigu periodu (datumu).	Range of time between a start date and an end date for which the account statement is issued
5.1.0	[1..1]	FromDateTime	<FrDtTm>	DateTime		
5.1.1	[1..1]	ToDateTime	<ToDtTm>	DateTime		
2.10	[1..1]	Account	<Acct>	+	Informācija par kontu	Unambiguous identification of the account to which credit and debit entries are made.
1.2.0	[1..1]	Identification	<Id>		Konta numurs IBAN formātā	Only IBAN allowed in Latvia.
1.2.1	[1..1]	IBAN	<IBAN>	Identifier		
1.2.8	[0..1]	Type	<Tp>		Konta tips- Depozīta konto, Kredītlīnijas kants utt.	... For example Current, Overdraft, Saving etc.
1.2.9	[1..1]	Code	<Cd>	Code	Pieļaujami blakus kolonnā minētie kontu kodi	Code Name Definition CACC Current Account used to post debits and credits when no specific account has been nominated. CASH CashPayment Account used for the payment of cash. CHAR Charges Account used for charges if different from the account for payment. CISH CashIncome Account used for payment of income if different from the current cash account. COMM Commission Account used for commission if different from the account for payment. LOAN Loan Account used for loans. MGLD MarginalLending Account used for a marginal lending facility.

						MOMA MoneyMarket Account used for money markets if different from the cash account. NREX NonResidentExternal Account used for non-resident external. ODFT Overdraft Account is used for overdrafts. ONDП OverNightDeposit Account used for overnight deposits. SACC Settlement Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system. SLRY Salary Accounts used for salary payments. SVGS Savings Account used for savings. TAXE Tax Account used for taxes if different from the account for payment.
1.2.11	[0..1]	Currency	<Ccy>	Code		
1.2.13	[0..1]	Owner	<Ownr>		Izmantojams, ja 1.3. laukā tiek norādīta pilnvarotā personā	Party that legally owns the account.
1.2.14	[0..1]	Name	<Nm>	Text	Vārds/nosaukums vai cita informācija, kas neapsaubāmi identifice konta īpašnieku	Name by which a party is known and which is usually used to identify that party.
1.2.26	[0..1]	Identification	<Id>			Unique and unambiguous identification of a party.
1.2.27	{Or}	[1..1]	OrganisationIdentification	<OrgId>		
1.2.28	[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).

1.2.29		[0..n]	Other	<Othr>			
1.2.30		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
1.2.31		[0..1]	SchemeName	<SchmeNm>			
1.2.32		[1..1]	Code	<Cd>	Code		
1.2.35	Or}	[1..1]	PrivateIdentification	<PrvtId>			
1.2.41		[0..n]	Other	<Othr>			
1.2.42		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
1.2.43		[0..1]	SchemeName	<SchmeNm>			
1.2.44		[1..1]	Code	<Cd>	Code		
1.2.56		[0..1]	Servicer	<Svcr>		Norādāma informācija par (trešo) pusi, kura apkalpo kontu- pārvalda grāmatvedības ierakstus, seko konta bilancei, kā arī sniedz informāciju.	Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.
1.2.57		[1..1]	FinancialInstitutionIdentification	<FinInstnId>		Finanšu institūcijas identifikators	Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised scheme.
1.2.58		[0..1]	BIC	<BIC>	Identifier	Bankas BIC 8 vai 11 simboli	BIC Identifier 8 or 11 symbols
1.2.64		[0..1]	Name	<Nm>	Text		
2.11		[0..1]	RelatedAccount	<RltdAcct>	+	Grupas konta gadījumā šo lauku var izmantot lai norādītu nākamā līmeņa konta numuru.	Identifies the parent account of the account for which the statement has been issued. <i>Usage:</i> In case if Group account is used, this tag can be used to indicate the next level account.

1.1.0		[1..1]	Identification	<Id>			
1.1.1		[1..1]	IBAN	<IBAN>	Identifier		
1.1.11		[0..1]	Currency	<Ccy>	Code	<p><i>Piezīme:</i> Valūta jānorāda tikai gadījumā, kerta pārskats/izraksts attiecas uz multivalūtu kontu</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p>	<p>Identification of the currency in which the account is held.</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p>
2.12		[0..n]	Interest	<Intrst>		<p>Šo lauku var izmantot gadījumā, ja sūta izrakstu par kredīta kontiem (2.10 - 1.2.9 kodi LOAN; ODFT; SVGS un citi).</p> <p>Par šī lauka izmantošanu jāvienojas ar banku</p>	<p>Set of elements used to provide general interest information that applies to the account at a particular moment in time.</p> <p>Usage of this should be bilaterally agreed between parties.</p>
2.13		[0..1]	Type	<Tp>			
2.14		[1..1]	Code	<Cd>	Code	INDY vai OVRN	INDY vai OVRN
2.16		[0..n]	Rate	<Rate>		Elementu kopums priekš procentu likmes norādišanas	Set of elements used to qualify the interest rate.
2.17		[1..1]	Type	<Tp>			
2.18	{Or	[1..1]	Percentage	<Pctg>	Rate		
2.19	Or}	[1..1]	Other	<Othr>	Text		
2.23		[1..n]	Balance	<Bal>		Elementu kopums bilances skaitliskai attēlošanai konkrētajā laika posmā	Set of elements used to define the balance as a numerical representation of the net increases and decreases in an account at a specific point in time.
2.24		[1..1]	Type	<Tp>		Bilances tips (pieejamais; iegrāmatotais atlikums utt.)	Specifies the nature of a balance.
2.25		[1..1]	CodeOrProprietary	<CdOrPrtry>			
2.26		[1..1]	Code	<Cd>	Code	Pārskats ir par nenoslēgtu periodu, tāpēc bankas izmanto dažādus atlautos	

						kodus no ISO saraksta. Par kodu izmantošanu jāvienojas individuāli.	
2.28	[0..1]	SubType	<SubTp>				
2.29	[1..1]	Code	<Cd>	Code			
2.31	[0..1]	CreditLine	<CdtLine>		Kredītlīnija/Overdrafts	Set of elements used to provide details on the credit line	
2.32	[1..1]	Included	<Incl>	Indicator	Norāda vai kredītlīnija tiek ierēķināta bilancē (vērtības True/False) Usage: If not present, credit line is not included in the balance amount. One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False	Indicates whether or not the credit line is included in the balance. Usage: If not present, credit line is not included in the balance amount. One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False	
2.33	[0..1]	Amount	<AmtCcy="AAA">	Amount	Kredītlīnijas/Overdrafa summa un valūta	Amount of money of the credit line	
2.34	[1..1]	Amount	<AmtCcy="AAA">	Amount	Konta bilance	Amount of money of the cash balance.	
2.35	[1..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda kredīta vai debeta bilanci. CRDT=bilances atlikums palielinās; DBIT=bilances atlikums samazinās. <i>Piezīme:</i> Nulles atlikums uzskatāms par pozitīvu atlikumu. Usage: A zero balance is considered to be a credit balance.	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.	
2.36	[1..1]	Date	<Dt>	+			
4.1.0	[1..1]	Date	<Dt>	DateTime			
2.43	[0..1]	TransactionsSummary	<TxSummry>				
2.49	[0..1]	TotalCreditEntries	<TtlCdtNtries>		Kopējā kredīta ierakstu summa un skaits	Specifies the total number and sum of credit entries.	
2.50	[0..1]	NumberOfEntries	<NbOfNtries>	Text	Ierakstu skaits	Number of individual entries included in the report.	
2.51	[0..1]	Sum	<Sum>	Quantity	Kopējā ierakstu summa	Total of all individual entries included in the report.	
2.52	[0..1]	TotalDebitEntries	<TtlDbtNtries>		Kopējā debeta ierakstu summa un skaits	Specifies the total number and sum of debit entries.	
2.53	[0..1]	NumberOfEntries	<NbOfNtries>	Text	Ierakstu skaits	Number of individual entries included in the report.	

2.54		[0..1]	Sum	<Sum>	Quantity	Kopējā ierakstu summa	Total of all individual entries included in the report.
2.76		[0..n]	Entry	<Ntry>		Lauks var būt tukšs, ja kontā nav bijis darījumu. <i>Piezīme.</i> Darījumu uzskaites sadaļa. Katrs darījums uzskaitās atsevišķi šādi ieraksti failā var būt no 0 (nav darījumu) līdz noteiktam daudzumam kuru banka spēj izdot vienā failā.	Can be absent if no movement for the account. For reporting single transaction or batch or collection of batches. If there are no transactions, we can send zeroes in header, and don't include this section at all
2.77		[0..1]	EntryReference	<NtryRef>	Text	Unikāla ieraksta reference viena izraksta ietvaros. <i>Piezīme.</i> Var būt ieraksta kārtas numurs	Unique reference for the entry <i>within one statement</i> . <i>Remark:</i> Can also be number of an entry.
2.78		[1..1]	Amount	<AmtCcy="AAA">	Amount	Summa konta valūtā	Amount in the currency of the account reported. Note: This amount can be Zero.
2.79		[1..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredīta vai Debeta (CRDT vai DBIT)	Indicates whether the balance is a credit or a debit balance.CRDT=Credit Operation is an increase.DBIT=Debit Operation is a decrease.Usage: A zero balance is considered to be a credit balance.
2.80		[0..1]	ReversallIndicator	<RvslInd>	Indicator	Norāda uz to vai darījums ir reverss (atgrieziem/atsaukiem darījumiem). <i>Piezīme:</i> lauks tie izmantots tikai tad, ja ieraksts ir saistīts ar atgrieztu darījumu.	Indicates whether or not the entry is the result of a reversal. Usage: This element should only be present if the entry is the result of a reversal. If the CreditDebitIndicator is CRDT and ReversallIndicator is Yes, the original operation was a debit entry. If the CreditDebitIndicator is DBIT and ReversallIndicator is Yes, the original operation was a credit entry. Data Type: One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False

2.81	[1..1]	Status	<Sts>	Code	Izmantotā vērtība BOOK, kā arī drīkst izmantot INFO un PDNG.	BOOK = Booked is required. Also used in camt.052 INFO = Information PDNG = Pending
2.82	[0..1]	BookingDate	<BookgDt>	+	Laiks, kad kontā izdarīts grāmatojums. <i>Piezīme:</i> Gaidāmais grāmatojuma datums, izņemot gadījumus, kad faktiski jau ir iegrāmatots.	Date and time when an entry is posted to an account on the account servicer's books. Usage: Booking date is the expected booking date, unless the status is booked, in which case it is the actual booking date.
4.1.0	[1..1]	Date	<Dt>	DateTime		
	[0..1]	ValueDate	<ValDt>	+	Var tik norādīts darījumiem ar pagātnes vai nākotnes value date.	Date at which assets become available to the account owner in case of a credit entry, or cease to beavailable to the account owner in case of a debit entry.
4.1.0	[1..1]	Date	<Dt>	DateTime		
2.84	[0..1]	AccountServicerReference	<AcctSvcrRef>	Text	Unikāls darījuma identifikators bankas ietvaros (piem. arhivārais Nr.) <i>Piezīme:</i> kad viens un tas pats ieraksts tiek parādīts gan camt.052, gan camt.053- tiem ir jāsakrīt	Unique reference as assigned by the account servicing institution to unambiguously identify the entry. <i>Recommendation:</i> When the same booked entry is reported in both the camt.052 or camt.054, the Account Service reference should be the same as reported in camt.053.
2.91	[1..1]	BankTransactionCode	<BkTxCd>		Vismaz vienam (Domain/Proprietary) jābūt izmantotam	Set of elements used to fully identify the type of underlying transaction resulting in an entry. Domain and/or proprietary may be provided. At least one must be provided.
2.92	[0..1]	Domain	<Domn>		Izmantoti atbilstoši ISO banku transakciju kodi	Recommendation suggested that standard BTC are used as first priority

2.93		[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.94		[1..1]	Family	<Fmly>			http://www.iso20022.org/external_code_list.page
2.95		[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.96		[1..1]	SubFamilyCode	<SubFmlyCd>	Code		http://www.iso20022.org/external_code_list.page
2.97		[0..1]	Proprietary	<Prtry>		Vieta kur var izmantot pašreiz lietotos kodus	<i>Remark:</i> For bank or community specific transaction coding
2.98		[1..1]	Code	<Cd>	Text		<i>Remark:</i> Code format is depending on the issuer. It may be a composite code.
2.99		[0..1]	Issuer	<Issr>	Text		Value samples (not exhausted):BAI = BAI CodeSWIFT = Swift CodeBBA = Belgian CodeCFONB = French CodeFFFS = Finnish CodeZKA = German CodeGVC = German CodeAEB = Spanish CodeDBA = Danish CodeAlso other values available such as bank name
2.135		[0..n]	EntryDetails	<NtryDtls>		Ja netiek lietota Pain.001 batch Booking iespēja, tad katram Entry (lauks 2.76) saistīts ir tikai viens lauks EntryDetails	This provides a breakdown of the transaction details when the entry is 'batched'. If the entry is not batched and transaction details are to be reported, then transaction details must only occur once.
2.136		[0..1]	Batch	<Btch>		Izmantojams transakciju detaļu norādīšanai faila maksājumu gadījumā	Set of elements used to provide details on batched transactions
2.137		[0..1]	Messageldentification	<MsglId>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 1.1 no "pain.001.001.03"	Point to point reference, as assigned by the sending party, to unambiguously identify the batch of transactions
2.138		[0..1]	PaymentInformationIdentification	<PmtInflId>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 2.1 no "pain.001.001.03"	Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message
2.139		[0..1]	NumberOfTransactions	<NbOfTxs>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 2.4 no "pain.001.001.03"	Number of individual transactions included in the batch
2.140		[0..1]	TotalAmount	<TtlAmtCcy="AAA">	Amount	<i>Piezīme:</i> Zinojuma elementa numurs 2.5 no "pain.001.001.03"	Total amount of money reported in the batch entry

2.141		[0..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredīta vai Debeta (CRDT vai DBIT)	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.
2.142		[0..n]	TransactionDetails	<TxDtls>			Set of elements used to provide information on the underlying transaction(s)
2.143		[0..1]	References	<Refs>			Set of elements used to provide the identification of the underlying transaction
2.144		[0..1]	Messagelidentification	<MsgId>	Text		Point to point reference, as assigned by the instructing party of the underlying message
2.145		[0..1]	AccountServicerReference	<AcctSvcrRef>	Text	Norādāma konkrēta maksājuma, kas iekļauts failā, reference.	Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction
2.146		[0..1]	PaymentInformationIdentification	<PmtInfId>	Text		Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message
2.147		[0..1]	InstructionIdentification	<InstrId>	Text	Unikāls transakcijas identifikators. <i>Piezīme:</i> Zinojuma elementa numurs 2.29 no "pain.001.001.03"	Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.
2.148		[0..1]	EndToEndIdentification	<EndToEndId>	Text	Unikāls maksājuma identifikators, kas tiek nodots caur visu maksājuma kēdi nemainīts. Tieks pārsūtīts tālāk tikai SEPA maksājumos. Laukā norādītais identifikators paredzēts, lai klients-klients posmā identificētu maksājumu. Ja netiek padots pain.001, tad atpakaļ padod NOT PROVIDED.Ne-SEPA maksājumos šis laiks tiek ignorēts. <i>Piezīme:</i> Zinojuma elementa numurs 2.30 no "pain.001.001.03"	Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. <i>Usage:</i> The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. <i>Usage:</i> In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. <i>Comment:</i> The end-to-end identification must be reported when it is known by the reporting bank. For SEPA the EndToEndId

							can be 'NOTPROVIDED'.
2.149	[0..1]	TransactionIdentification	<TxId>	Text		Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.	
2.150	[0..1]	MandateIdentification	<MndtId>	Text	Priekš SEPA tiešā debeta darījumiem	Unique identification, as assigned by the creditor, to unambiguously identify the mandate. <i>Comment:</i> For reporting SEPA Direct Debits, as appropriate	
2.153	[0..1]	Proprietary	<Prtry>		Reference, kas attiecināma uz konkrēto maksājumu	Proprietary reference related to the underlying transaction.	
2.154	[1..1]	Type	<Tp>	Text			
2.155	[1..1]	Reference	<Ref>	Text			
2.156	[0..1]	AmountDetails	<AmtDtls>	+		Set of elements providing detailed information on the original amount. Usage: This component (on transaction level) should be used in case booking is for a single transaction and the original amount is different from the entry amount. It can also be used in case individual original amounts are provided in case of a batch or aggregate booking. Comment: All Amount Details are in all cases given on the	

						Transaction Details level on single and batch bookings. For consistency purposes Entry/Amount information is repeated at TransactionDetails/AmountDetails/TransactionAmount.
2.1.0	[0..1]	InstructedAmount	<InstdAmt>		Izmanto: -) lai norādītu sākotnējo summu, ja maksājums uzsākts citā valūtā;-) ja maksājums ir tajā pašā valūtā, lai norādītu bruto summu (t.i., summu pirms komisiju ieturēšanas). Piemēram, starpbanku MT103 ziņojuma šī summa ziņo par 33.b lauku saturu. Norādītās summas var izlaist tādā gadījumā, ja nav ieturēta komisija vai arī maksājumu apstrādes procesā nav notikusi konvertācija.	<i>Usage:</i> Used for original amount in original currency and is the gross value (i.e. prior to application of charges) in same currency situations. For example in the inter-bank MT103 message this amount reports the 33B field contents. Instructed Amount may be omitted in the case when there are no charges or no FX. In FX cases the booked transaction FX information can be found with TransactionAmount. When account servicing bank is receiving a transaction via MT103, it might contain other FX information of sender bank FX operation. This is only in the situation of original payment initiation done with Equivalent amount.
2.1.1	[1..1]	Amount	<AmtCcy="AAA">	Amount		
2.1.2	[0..1]	CurrencyExchange	<CcyXchg>			
2.1.3	[1..1]	SourceCurrency	<SrcCcy>	Code	Valūta, no kurās tiek veikta konvertācija	Currency from which an amount is to be converted in a currency conversion.
2.1.4	[0..1]	TargetCurrency	<TrgtCcy>	Code	Valūta, uz kuru tiek veikta konvertācija	Currency into which an amount is to be converted in a currency conversion.
2.1.5	[0..1]	UnitCurrency	<UnitCcy>	Code		
2.1.6	[1..1]	ExchangeRate	<XchgRate>	Rate		
2.1.7	[0..1]	ContractIdentification	<CtrctId>	Text	Piezīme: Ziņojuma elementa numurs 2.50 no "pain.001.001.03"	Unique identification to unambiguously identify the foreign exchange contract.
2.1.9	[0..1]	TransactionAmount	<TxAmt>		Norādām transakciju konta valūtā un par attiecīgo summu	Amount of the underlying transaction. <i>Remark:</i> EPC Mandated for SEPA payments. Recommendation: This amount is to be used for matching and aggregation purpose and it is used in all cases when AmountDetails structure is used. It is always in the currency of the account

					reported and the Entry Amount and populated in all Transaction Details—cases when AmountDetails structure is used. It is the net amount of the underlying transaction including charges expressed in the currency of the posting account. This will apply both Single Bookings and Batch Bookings with underlying transactions. This amount indicates the value that has been debited from or credited to reported bank account (booked or posted amount). Note: this information may be duplicate with Entry/Amount if the single booking is in the same currency as reported account currency is.
2.1.10	[1..1]	Amount	<AmtCcy="AAA">	Amount	
2.1.11	[0..1]	CurrencyExchange	<CcyXchg>		
2.1.12	[1..1]	SourceCurrency	<SrcCcy>	Code	
2.1.13	[0..1]	TargetCurrency	<TrgtCcy>	Code	
2.1.14	[0..1]	UnitCurrency	<UnitCcy>	Code	
2.1.15	[1..1]	ExchangeRate	<XchgRate>	Rate	
2.1.16	[0..1]	ContractIdentification	<CtrctId>	Text	
2.1.17	[0..1]	QuotationDate	<QtnDt>	DateTime	
2.163	[0..1]	BankTransactionCode	<BkTxCd>		<i>Piezīme:</i> Satur to pašu informāciju, kas 2.91. Taču tā var būt atšķirīga Batch Booking gadījumā.
2.164	[0..1]	Domain	<Domn>		Recommendation suggested that standard BTC are used as first priority
2.165	[1..1]	Code	<Cd>	Code	http://www.iso20022.org/external_code_list.page
2.166	[1..1]	Family	<Fmly>		http://www.iso20022.org/external_code_list.page
2.167	[1..1]	Code	<Cd>	Code	http://www.iso20022.org/external_code_list.page
2.168	[1..1]	SubFamilyCode	<SubFmlyCd>	Code	http://www.iso20022.org/external_code_list.page

2.169		[0..1]	Proprietary	<Prtry>			Remark: For bank or community specific transaction coding
2.170		[1..1]	Code	<Cd>	Text		Remark: Code format is depending on the issuer. It may be a composite code.
2.171		[0..1]	Issuer	<Issr>	Text		
2.172		[0..n]	Charges	<Chrgs>			
2.173		[0..1]	TotalChargesAndTaxAmount	<TtlChrgsAndTaxAmtCcy="AAA">	Amount		
2.174		[1..1]	Amount	<AmtCcy="AAA">	Amount		
2.175		[0..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredita vai Debeta (CRDT vai DBIT)	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.
2.176		[0..1]	Type	<Tp>			Specifies the type of charge
2.177		[1..1]	Code	<Cd>	Code		BRKF - Brokerage Fee COMM - Commission. Used in case of incoming cardpayment
2.181		[0..1]	Party	<Pty>	+		Party that takes the transaction charges or to which the transaction charges are due
6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		BIC of financial institution debiting the charges If not informed, the charge is taken by creditor bank.
6.1.7		[0..1]	Name	<Nm>	Text		
2.199		[0..1]	RelatedParties	<RltdPties>			
2.200		[0..1]	InitiatingParty	<InitgPty>	+	lenākošajiem maksājumiem tiek pievienots, ja ir pieejams. Izejošajiem maksājumiem: Initiating party <InitgPty> no pain.001, ja ir pieejams (lauks 1.8)	For incoming payments is reported if available. For outgoing payments: Initiating party <InitgPty> from pain.001, if available (tag 1.8)
9.1.0		[0..1]	Name	<Nm>	Text		

9.1.12		[0..1]	Identification	<Id>			
9.1.13		[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18		[1..1]	Code	<Cd>	Code		
2.201		[0..1]	Debtor	<Dbtr>	+	lenākošajiem maksājumiem: Nosaukums, adrese un identifikators tiek norādīti, ja ir pieejami. Izejošajiem maksājumiem: Netiek lietots (informācija tiek parādīta blokā Account Owner)	For incoming payments name, address and ID are reported if available. For outgoing payments: Not used
9.1.0		[0..1]	Name	<Nm>	Text		
9.1.1		[0..1]	PostalAddress	<PstlAdr>			
9.1.2		[0..1]	AddressType	<AdrTp>	Code		
9.1.3		[0..1]	Department	<Dept>	Text		
9.1.4		[0..1]	SubDepartment	<SubDept>	Text		
9.1.5		[0..1]	StreetName	<StrtNm>	Text		
9.1.6		[0..1]	BuildingNumber	<BldgNb>	Text		
9.1.7		[0..1]	PostCode	<PstCd>	Text		
9.1.8		[0..1]	TownName	<TwnNm>	Text		
9.1.9		[0..1]	CountrySubDivision	<CtrySubDvsn>	Text		
9.1.10		[0..1]	Country	<Ctry>	Code		
9.1.11		[0..7]	AddressLine	<AdrLine>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or}	[1..1]	OrganisationIdentification	<OrgId>			
		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		

9.1.14							
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis lauks satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	If tax payer ID provided, then TXID indicated. Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalOrganisationIdentification1Code
9.1.19	Or}}	[1..1]	Proprietary	<Prtry>	Text		
9.1.20		[0..1]	Issuer	<Issr>	Text		
9.1.21	Or}	[1..1]	PrivateIdentification	<PrvtId>			
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>			
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text		
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		
9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis lauks satur NIDN. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page in worksheet ExternalPersonIdentification1Code	If personal code provided, then NIDN indicated. Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalPersonIdentification1Code

						rnal_code_list.page sarakstā ExternalPersonIdentification 1Code	
9.1.31	Or}}	[1..1]	Proprietary	<Prtry>	Text		
9.1.32		[0..1]	Issuer	<Issr>	Text		
2.202		[0..1]	DebtorAccount	<DbtrAcct>	+	Ienākošajiem maksājumiem: kunts tiek norādīts, ja ir pieejams. Izejošajiem maksājumiem: Netiek lietots (informācija tieka parādīta kontā pārskata/izraksta līmenī)	For incoming payments account is reported if available. For outgoing payments: Not used
1.1.0		[1..1]	Identification	<Id>			
1.1.1	{Or	[1..1]	IBAN	<IBAN>	Identifier		
1.1.2	Or}	[1..1]	Other	<Othr>			
1.1.3		[1..1]	Identification	<Id>	Text		
1.1.4		[0..1]	SchemeName	<SchmeNm>			
1.1.5		[1..1]	Code	<Cd>	Code		
2.203		[0..1]	UltimateDebtor	<UltmtDbtr>	+	Tikai SEPA maksājumiem. Tiek norādīts gadījumos ja sanemts ienākošajā maksājumā, vai Maksātājs norādījis izejošajā maksājumā. Vērtība no laukiem 2.70 vai 2.23, ja maksājums iesūtīts ar pain.001 un ir norādīts	Ultimate party that owes an amount of money to the (ultimate) creditor. EPC mandated for SEPA Payment. In instances where the ReversalIndicator <Rvslnd> is TRUE, the Ultimate Creditor and Ultimate Debtor must be the same as the Ultimate Creditor and Ultimate Debtor of the original entry.
9.1.0		[0..1]	Name	<Nm>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or	[1..1]	OrganisationIdentification	<OrgId>			

9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18		[1..1]	Code	<Cd>	Code		
9.1.21	Or}	[1..1]	PrivatIdentification	<PrvtId>			
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>			
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text		
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		
9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30		[1..1]	Code	<Cd>	Code		
2.204		[0..1]	Creditor	<Cdtr>	+	Ienākošiem maksājumiem tiek norādīts kā konta īpašnieks. Izejošiem maksājumiem norāda klienta doto informāciju (vērtība no lauka 2.79, ja maksājums iesūtīts ar pain.001)	For outgoing payments details are taken from tag 2.79 from pain.001. For incoming payments: Not used.
9.1.0		[0..1]	Name	<Nm>	Text	Pārskata/izraksta lauks 2.10; apakšlauks 1.2.13	
9.1.1		[0..1]	PostalAddress	<PstlAdr>			
9.1.10		[0..1]	Country	<Ctry>	Code		
9.1.11		[0..7]	AddressLine	<AdrLine>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or	[1..1]	OrganisationIdentification	<OrgId>			
		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by

9.1.14							the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis laiks satur TXID. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	If tax payer ID provided, then TXID indicated. Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalOrganisationIdentification1Code
9.1.19	Or}}	[1..1]	Proprietary	<Prtry>	Text		
9.1.20		[0..1]	Issuer	<Issr>	Text		
9.1.21	Or}	[1..1]	PrivateIdentification	<PrvId>		Privātpersonas Identifikators	
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		Informācija par dzimšanas vietu un laiku	
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text	Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		
9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas	If personal code provided, then NIDN indicated.

						kods, šis lauks satur NIDN. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalPersonIdentification1Code
9.1.31	Or}}	[1..1]	Proprietary	<Prtry>	Text	Identifikācijas shēmas nosaukums brīvā tekstā	
9.1.32		[0..1]	Issuer	<Issr>	Text		
9.1.33		[0..1]	CountryOfResidence	<CtryOfRes>	Code	Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	
2.205		[0..1]	CreditorAccount	<CdtrAcct>	+	Ienākošiem maksājumiem tieki norādīts konta pārskata/izraksta līmenī (lauks 2.10). Izejošiem maksājumiem norāda klienta doto informāciju (vērtība no lauka 2.80, ja maksājums iesūtīts ar pain.001) Obligāti jālieto IBAN priekš SEPA maksājumiem	For outgoing payments account is taken from tag 2.80 from pain.001. IBAN usage mandatory for SEPA payments For incoming payments: Not used.
1.1.0		[1..1]	Identification	<Id>			
1.1.1	{Or	[1..1]	IBAN	<IBAN>	Identifier		
1.1.2	Or}	[1..1]	Other	<Othr>		Izmanto, ja nav pieejams IBAN.	If IBAN not used
1.1.3		[1..1]	Identification	<Id>	Text		
1.1.4		[0..1]	SchemeName	<SchmeNm>			
1.1.5		[1..1]	Code	<Cd>	Code		
2.206		[0..1]	UltimateCreditor	<UltmtCdr>	+	Tikai SEPA maksājumiem. Tiek norādīts gadījumos ja saņemts ienākošajā maksājumā, vai Maksātājs norādījis izējošajā maksājumā.	Ultimate party to which an amount of money is due. EPC Mandated for SEPA Payments. In instances where the ReversallIndicator <RvslInd> is TRUE, the Ultimate Creditor and Ultimate Debtor must be the same as the Ultimate

						<i>Piezīme:</i> vērtība no lauka 2.81, ja maksājums iesūtīts ar pain.001	Creditor and Ultimate Debtor of the original entry.
9.1.0	[0..1]	Name	<Nm>	Text			
9.1.12	[0..1]	Identification	<Id>				
9.1.13	{Or	[1..1] OrganisationIdentification	<OrgId>				
9.1.14	[0..1]	BICOrBEI	<BICOrBEI>	Identifier			
9.1.15	[0..n]	Other	<Othr>				
9.1.16	[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID	
9.1.17	[0..1]	SchemeName	<SchmeNm>				
9.1.18	[1..1]	Code	<Cd>	Code			
9.1.21	Or}	[1..1] PrivateIdentification	<PrvtId>				
9.1.22	[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>				
9.1.23	[1..1]	BirthDate	<BirthDt>	DateTime			
9.1.25	[1..1]	CityOfBirth	<CityOfBirth>	Text			
9.1.26	[1..1]	CountryOfBirth	<CtryOfBirth>	Code			
9.1.27	[0..n]	Other	<Othr>				
9.1.28	[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person	
9.1.29	[0..1]	SchemeName	<SchmeNm>				
9.1.30	[1..1]	Code	<Cd>	Code			
2.211	[0..1]	RelatedAgents	<RltdAgt>				
2.212	[0..1]	DebtAgent	<DbtrAgt>	+	Izmanto tikai ienākošajiem maksājumiem, lai norādītu maksātāja banku.	EPC Mandated for SEPA CT and DD. One of the following must be provided - BIC or Clearing System Member or Name. In instances where the ReversalIndicator <RvslInd> is TRUE, the Creditor Agent and Debtor Agent must be the same as the Creditor Agent and Debtor Agent of the original entry.	

6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		
6.1.7		[0..1]	Name	<Nm>	Text		
2.213		[0..1]	CreditorAgent	<CdtrAgt>	+	Izmanto tikai izejošajiem maksājumiem, lai norādītu saņēmējbanku. <i>Piezīme:</i> vērtība no lauka 2.77, ja maksājums iesūtīts ar pain.001	EPC Mandated for SEPA CT and DD. In instances where the ReversalIndicator <RvslInd> is TRUE, the Creditor Agent and Debtor Agent must be the same as the Creditor Agent and Debtor Agent of the original entry.
6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		
6.1.2		[0..1]	ClearingSystemMemberIdentification	<ClrSysMmbld>			
6.1.3		[0..1]	ClearingSystemIdentification	<ClrSysId>			
6.1.4		[1..1]	Code	<Cd>	Code		
6.1.6		[1..1]	MemberIdentification	<Mmbld>	Text		
6.1.7		[0..1]	Name	<Nm>	Text		
6.1.8		[0..1]	PostalAddress	<PstlAdr>			
6.1.17		[0..1]	Country	<Ctry>	Code		
6.1.18		[0..7]	AddressLine	<AdrLine>	Text		
2.224		[0..1]	Purpose	<Purp>		<i>Piezīme:</i> vērtība no lauka 2.86, ja maksājums iesūtīts ar pain.001	<i>Remark:</i> in case of outgoing value from tag 2.86 from pain.001
2.225	{Or}	[1..1]	Code	<Cd>	Code		
2.226	Or}	[1..1]	Proprietary	<Prtry>	Text		
2.234		[0..1]	RemittanceInformation	<RmtInf>		<i>Piezīme:</i> vērtība no lauka 2.98, ja maksājums iesūtīts ar pain.001	<i>Remark:</i> in case of outgoing value from tag 2.98 from pain.001

					Izņēmums: Valsts kases gadījumā šī sadāļa tiek izmantota arī EKK un ar to saistītās informācijas atspoguļošanai. Informācija, kas paredzēta laukā 2.236 (un zemāk), tiek atspoguļota laukā 2.235	Exception: In case of StateTreasury this component is also used to display information about EKK (ECC - Economic Classification Code) and the information related to it. The information that is meant for tag 2.236 (and below) is displayed in 2.235
2.235	[0..n]	Unstructured	<Ustrd>	Text	<p>Izmantojam to pašu logiku, ko maksājuma iniciēšanas failā- lauka garums ne vairāk par 140.</p> <p><i>Piezīme:</i> vērtība no lauka 2.99, ja maksājums iesūtīts ar pain.001</p> <p>Izņēmums: Valsts kases gadījumā tiek izmantoti vairāki (atkārtoti) sadalas ieraksti, lai atspoguļotu nestukturēto <u>VAL</u> struktūrēto informāciju, kā arī, lai atspoguļotu EKK un to pavadošo informāciju. Piemēru skatīt zemāk.</p>	Length of field limited to 140 characters. <i>Remark:</i> in case of outgoing value from tag 2.99 from pain.001 Exception: In case of StateTreasury the tag is used for several times in order to display unstructured <u>OR</u> - structured information as well as EKK (ECC - Economic Classification Code) and the information related to it. Please see below for example.
2.236	[0..n]	Structured	<Strd>		<p><i>Piezīme:</i> vērtība no lauka 2.100, ja maksājums iesūtīts ar pain.001</p> <p>Izņēmums: Valsts kases gadījumā netiek izmantots. Ja maksājums iesūtīts ar pain.001, tad šai sadalai paredzēto informāciju attēlo laukā 2.235, pierakstā /RFB/XXXXX, kur X ir vērtība no pain.001 lauka 2.100</p>	<i>Remark:</i> in case of outgoing value from tag 2.100 from pain.001 Exception: In case of StateTreasury this component is not used. If payment is imported with pain.001, then the information supposed for this tag is displayed in tag 2.235 in the following format: /RFB/XXXXX, where X is the value from tag 2.100 in pain.001
2.237	[0..n]	ReferredDocumentInformation	<RfrdDocInf>			
2.238	[0..1]	Type	<Tp>			
2.239	[1..1]	CodeOrProprietary	<CdOrPrtry>			
2.240	{Or [1..1]}	Code	<Cd>	Code		
2.241	Or} [1..1]	Proprietary	<Prtry>	Text		
2.243	[0..1]	Number	<Nb>	Text		
2.244	[0..1]	RelatedDate	<RltdDt>	DateTime		
2.245	[0..1]	ReferredDocumentAmount	<RfrdDocAmt>			
2.246	[0..1]	DuePayableAmount	<DuePyblAmtCcy="AAA">	Amount		
2.248	[0..1]	CreditNoteAmount	<CdtNoteAmtCcy="AAA">	Amount		

2.255		[0..1]	RemittedAmount	<RmtdAmtCcy="AAA">	Amount		
2.256		[0..1]	CreditorReferenceInformation	<CdtrRefInf>		Piezīme: vērtība no lauka 2.120, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.120 from pain.001
2.257		[0..1]	Type	<Tp>		Piezīme: vērtība no lauka 2.121, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.121 from pain.001
2.258		[1..1]	CodeOrProprietary	<CdOrPrtry>		Piezīme: vērtība no lauka 2.122, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.122 from pain.001
2.259		[1..1]	Code	<Cd>	Code	Piezīme: vērtība no lauka 2.123, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.123 from pain.001
2.261		[0..1]	Issuer	<Issr>	Text	Piezīme: vērtība no lauka 2.125, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.125 from pain.001
2.262		[0..1]	Reference	<Ref>	Text	Piezīme: vērtība no lauka 2.126, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.126 from pain.001
2.265		[0..3]	AdditionalRemittanceInformation	<AddtlRmtlInf>	Text		
2.293		[0..1]	ReturnInformation	<Rtrlnf>		Norāda informāciju saistītu ar maksājuma atgriešanu	Report when available for return items
2.304		[0..1]	Reason	<Rsn>		Norāda maksājuma atgriešanas kodu. Kodi pieejami http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Specifies Reason for Return. Valid codes available at http://www.iso20022.org/external_code_list.page in a worksheet ExternalReturnReason1Code
2.305	{Or}	[1..1]	Code	<Cd>	Code		
2.306	Or}	[1..1]	Proprietary	<Prtry>	Text		
2.307		[0..n]	AdditionalInformation	<AddtlInf>	Text		
2.313		[0..1]	AdditionalTransactionInformation	<AddtlTxlnf>	Text	Priekš EKK koda norādišanas komercbankās (Valsts Kases gadījumā skaiti aprakstu pie 2.234) <i>Piemērs: //EKK/12345/</i>	To be used to indicate EKK by banks (In case of State Treasury see description under 2.234)

EKK kodu lietošanas piemērs Valsts Kasē

```
<RmtInf>
  <Ustrd>/RFB/RF0243256216</Ustrd>
  <!-- ja no PAIN 0001 ienāk kā Strd, tad CAMT attēlo Ustrd -->
  <Ustrd>/šeit tiek ierakstīts maksājuma mērķis nestrukturētā veidā</Ustrd>
  <!-- ja no PAIN 001 ienāk kā Ustrd, tad CAMT attēlo Ustrd -->
  <Ustrd>/EKKACC/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
  <Ustrd>/EKKACC/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
  <Ustrd>/EKKPMT/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
  <Ustrd>/EKKPMT/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
  <Ustrd>/EKKLOC/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
  <Ustrd>/EKKLOC/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
</RmtInf>
```

Konta pārskata ziņojuma paraugs

```
<?xml version="1.0" encoding="UTF-8"?>
<Document>
  <BkToCstmrAcctRpt>
    <GrpHdr>
      <MsgId>STMT20130710193521</MsgId>
      <CreDtTm>2001-12-17T09:30:47Z</CreDtTm>
    </GrpHdr>
    <Rpt>
      <Id>5074322222537</Id>
      <CreDtTm>2001-12-17T09:30:47Z</CreDtTm>
      <FrToDt>
        <FrDtTm>2001-12-17T09:30:47Z</FrDtTm>
        <ToDtTm>2001-12-17T09:30:47Z</ToDtTm>
      </FrToDt>
      <Acct>
        <Id>
          <IBAN>LV12TEST000000000001</IBAN>
        </Id>
        <Ccy>USD</Ccy>
        <Svcr>
          <FinInstnId>
            <BIC>TESTLV22</BIC>
          </FinInstnId>
        </Svcr>
      </Acct>
      <Bal>
        <Tp>
          <CdOrPrtry>
            <Cd>OPBD</Cd>
          </CdOrPrtry>
        </Tp>
        <Amt Ccy="USD">500</Amt>
        <CdtDbtInd>CRDT</CdtDbtInd>
        <Dt>
          <Dt>2001-12-17</Dt>
        </Dt>
      </Bal>
    <!-- transakcija bez konvertācijas -->
```

```

<Ntry>
  <Amt Ccy="USD">3</Amt>
  <CdtDbtInd>DBIT</CdtDbtInd>
  <Sts>BOOK</Sts>
  <BookgDt>
    <Dt>2001-12-17</Dt>
  </BookgDt>
  <!-- transakcijas unikālais identifikators -->
  <AcctSvcrRef>123456789</AcctSvcrRef>
  <BkTxCd>
    <Domn>
      <Cd>PMNT</Cd>
      <Fmly>
        <Cd>CCRD</Cd>
        <SubFmlyCd>FEES</SubFmlyCd>
      </Fmly>
    </Domn>
  </BkTxCd>
  <NtryDtls>
    <TxDtls>
      <RmtInf>
        <Ustrd>Komisijas maksā</Ustrd>
      </RmtInf>
    </TxDtls>
  </NtryDtls>
</Ntry>
<!-- transakcija ar konvertāciju -->
<Ntry>
  <!-- summa konta valūtā -->
  <Amt Ccy="USD">128.2</Amt>
  <CdtDbtInd>DBIT</CdtDbtInd>
  <Sts>BOOK</Sts>
  <BookgDt>
    <Dt>2001-12-17</Dt>
  </BookgDt>
  <AcctSvcrRef>12334567234</AcctSvcrRef>
  <BkTxCd>
    <Domn>
      <Cd>PMNT</Cd>
      <Fmly>
        <Cd>ICDT</Cd>
        <SubFmlyCd>DMCT</SubFmlyCd>
      </Fmly>

```

```

        </Domn>
</BkTxCd>
<NtryDtls>
    <TxDtls>
        <Refs>
            <EndToEndId>34</EndToEndId>
        </Refs>
        <!-- to visu bloku rādam tikai gadījumā ja bija konvertācija -->
        <AmtDtls>
            <InstdAmt>
                <!-- cik panemts no klienta (transakcijas valūtā) -->
                <Amt Ccy="EUR">100</Amt>
            </InstdAmt>
            <TxAmt>
                <!-- summa konta valūtā -->
                <Amt Ccy="USD">128.2</Amt>
                <!-- detaļas par konvertāciju -->
                <CcyXchg>
                    <!-- no kuras valūtas konvertācija -->
                    <SrcCcy>USD</SrcCcy>
                    <!-- uz kuru valūtu -->
                    <TrgtCcy>EUR</TrgtCcy>
                    <!-- pret kuras valūtas tika norādīts kurss (1 EUR = 1.282 USD) -->
                    <UnitCcy>USD</UnitCcy>
                    <!-- kurss -->
                    <XchgRate>1.282</XchgRate>
                </CcyXchg>
            </TxAmt>
        </AmtDtls>
        <RltdPties>
            <Cdtr>
                <Nm>Gatis Egle</Nm>
                <Id>
                    <PrvtId>
                        <Othr>
                            <Id>121212-12121</Id>
                        </Othr>
                    </PrvtId>
                </Id>
            </Cdtr>
            <CdtrAcct>
                <Id>
                    <IBAN>LV21TEST00000000000002</IBAN>

```

```
</Id>
</CdtrAcct>
</RltdPties>
<RmtInf>
    <Ustrd>Parvedums ar konvertaciju</Ustrd>
</RmtInf>
<TxDtls>
<NtryDtls>
<Ntry>
</Rpt>
</BkToCstmrAcctRpt>
</Document>
```

Piemērs camt.060.001.03 ziņojuma izmantošanai.

```
<?xml version="1.0" encoding="UTF-8"?>
<Document>
  <AcctRptgReq>
    <GrpHdr>
      <MsgId>687a6d87a6da876da8d68</MsgId>
      <CreDtTm>2014-03-04T12:34:56</CreDtTm>
    </GrpHdr>
    <RptgReq>
      <ReqdMsgNmId>camt.052.001.01</ReqdMsgNmId>
      <Acct>
        <!-- Obligāts bloks (pēc biznes-loģikas) -->
        <Id>
          <IBAN> LV12TEST000000000001</IBAN>
          <!-- Konta numurs -->
        </Id>
        <Ccy>EUR</Ccy>
        <!-- Valūta. Ja nav aizpildīts - pārskatā būs visas kontam pieejamas valūtas -->
      </Acct>
      <AcctOwnr>
        <!-- Obligāts bloks (pēc shēmas), bet tiek ignorēts -->
        <Pty/>
      </AcctOwnr>
      <RptgPrd>
        <FrToDt>
          <!-- Datumi no-līdz -->
          <FrDt>2013-01-01</FrDt>
          <ToDt>2013-12-31</ToDt>
        </FrToDt>
        <FrToTm>
          <!-- Laiks, no kurā interesē transakcijas (ja par visu dienu - 00:00:00) -->
          <FrTm>00:00:00</FrTm>
        </FrToTm>
        <Tp>ALLL</Tp>
      </RptgPrd>
    </RptgReq>
  </AcctRptgReq>
</Document>
```

4. Konta izraksta ziņojums

camt.053.001.02

Konta izraksta ziņojuma satura apraksts

Konta izraksta ziņojumu nosūta konta uzturētājs (kredītiestāde) konta īpašiekam vai tā pilnvarotai pusei. Šo ziņojumu izmanto, lai informētu konta īpašnieku, vai tā pilnvarotās personas par kontā veiktiem grāmatojumiem un par konta bilanci noteiktā laikā.

Konta izraksta ziņojums var saturēt informāciju par vairāk nekā vienu kontu. Tas sniedz informāciju, kas nepieciešama naudas plūsmas pārvaldībai un/vai bankas ierakstu saskaņošanu ar klienta datiem. Konta izraksts atspoguļo tikai iegrāmatotos darījumus un konta bilanci. Izrakstā var tikt iekļauta papildu detalizēta informācija par tajā atspoguļotajiem ierakstiem.

Konta izraksta ziņojumus nosūta pēc iepriekš starp klientu un banku saskaņota grafika, piemēram, vienas dienas ietvaros. Minētos ziņojumus var saņemt arī persona, kas nav konta īpašnieks, taču tai ir konta īpašnieka pilnvara šāda satura informācijas saņemšanai.

Ziņojums satur divus obligātos blokus: Galvene (Header) un Pārskats (Account Report)

Galvene (Header): Šis bloks ir obligāts un tiek norādīts tikai vienu reizi. Tas satur faila identificējošus elementus – ziņojuma identifikators, ziņojuma izveides datums un laiks.

Konta pārskats (Account Report): Šis bloks ir obligāts un var tikt norādīts arī atkārtoti. Tas ir norādāms atkārtoti par katru pārskatā atspoguļoto kontu. Pārskats satur komponentes Bilance un leraksts.

Zemāk parādītajā tabulā aprakstīti ziņojumos izmantotie lauki sekojošā formātā:

ISO Index	Or	Mult.	Ziņojuma elements	XML Tag	Tips	Komentāri par laukā ievadāmo informāciju (LAT/ENG)
		[1..1]	Message root	<BkToCstmrStmt>		

Ind. – Ziņojuma elementa numurs. Numurs atbilst ISO 20022 XML Ziņojumu aprakstam, kurš ir atrodams vietnē http://www.iso20022.org/message_archive.page#first_version_bam zem "Second version of the Bank-to-Customer Cash Management messages" ar atsauci "camt.052.001.02".

Or. – Norāda uz izvēlni. Ziņojumā var tikt iekļauts viens vai otrs elements.

Mult. – Norāda uz elementa izmantošanas obligātumu un šī elementa parādīšanās biežumu. Iespējamās vērtības un to nozīme:

- [1..1] – Elements ir obligāts un var tikt norādīts vienu reizi;
- [1..n] - Elements ir obligāts un var tikt norādīts vienu vai vairākas reizes;
- [0..1] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts tikai vienu reizi;
- [0..n] – Elementu drīkst nenorādīt. Ja elements tiek norādīts, tas var būt darīts vienu vai vairākas reizes.

Ziņojuma elements – Elementa nosaukums atbilstoši ISO 20022 XML

XML Tag – Atbilstošā elementa XML tags ziņojumā

Tips – XML tagā ievadītās informācijas apraksts

Komentāri – Papildus komentāri par lauka aizpildīšanu.

Piezīme: Bankas, atsevišķi vienojoties ar klientiem, var izmantot camt.060.001.03 ziņojumu, lai strukturētā veidā pieprasītu konta izrakstu. Piemēru skatīt zemāk

ISO Index	Or	Mult.	Ziņojuma elements (Message Item)	XML Tag	Tips (Type)	Komentāri par laukā ievadāmo informāciju [LAT]	Comments about the tag
1.0		[1..1]	GroupHeader	<GrpHdr>			
1.1		[1..1]	MessageIdentification	<MsgId>	Text	Reference, kuru piešķir kontu apkalpojošā institūcija un, kas tiek nosūtīta konta īpašniekam vai pilnvarotai personai, un, kam ir nepārprotami jāidentificē ziņojums. Usage: The account servicing institution has to make sure that MessageIdentification is unique per account owner for a pre-agreed period.	Point to point reference, as assigned by the account servicing institution, and sent to the account owner or the party authorised to receive the message, to unambiguously identify the message.
1.2		[1..1]	CreationDateTime	<CreDtTm>	DateTime	Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss, piemēram: 2012-11-21T09:10:49)	Date and time at which the message was created (DDDD-MM-DDThh:mm:ss, example: 2012-11-21T09:10:49).
1.3		[0..1]	MessageRecipient	<MsgRcpt>	+	Jānorāda, ja ziņojuma saņēmējs ir konta īpašnieka pilnvarotā puse. <i>Piezīme:</i> Izmantojam tikai gadījumā, ja izraksta saņēmējs nav konta īpašnieks Usage: MessageRecipient should only be identified when different from the account owner	Party authorised by the account owner to receive information about movements on the account.
9.1.0		[0..1]	Name	<Nm>	Text	Vārds/nosaukums vai cita informācija, kas neapšaubāmi identificē maksājuma iniciatoru.	Name by which a party is known and which is usually used to identify that party.
9.1.12		[0..1]	Identification	<Id>			
9.1.13		[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).
9.1.15		[0..n]	Other	<Othr>			

9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18		[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis laiks satur TXID. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	Codes can be found at http://www.iso20022.org/external_code_list.page in worksheet ExternalOrganisationIdentification1Code
1.4		[0..1]	MessagePagination	<MsgPgtn>	+	Lauks var noderēt ja tiek ģenerēts izraksts par lielu skaitu darījumu konkrētā periodā, un sistēma, caur kuru izraksts tiek ģenerēts, nespēj apstrādāt tik lielu ierakstu apjomu (piemēram 30K rindīgu izraksts, kamēr sistēma maksimāli spēj apstrādāt tikai 10K). Aktuāli lielajiem klientiem.	Set of elements used to provide details on the page number of the message. Usage: The pagination of the message is only allowed when agreed between the parties.
8.1.0		[1..1]	PageNumber	<PgNb>	Text		Page number
8.1.1		[1..1]	LastPageIndicator	<LastPgInd>	Indicator	Identificē pēdējo lapu (Yes/No)	Indicates the last page
2.0		[1..n]	Statement	<Stmt>			
2.1		[1..1]	Identification	<Id>	Text	Unikāls ziņojuma identifikators, ko piešķir konta turētājs (kredītiestāde)	Unique identification, as assigned by the account servicer, to unambiguously identify the account statement
2.2		[0..1]	ElectronicSequenceNumber	<ElctrncSeqNb>	Quantity	Pārskata/izraksta kārtas skaitlis, kas pieaug ar katru nākamo pārskatu/izrakstu.	Sequential number of the statement, as assigned by the account servicer. Usage: The sequential number is increased incrementally for each statement sent electronically.
2.4		[1..1]	CreationDateTime	<CreDtTm>	DateTime	Laiks un datums, kad ziņojums izveidots (GGGG-MM-DDThh:mm:ss, piemēram: 2012-11-	Date and time at which the message was created.

						21T09:10:49)	
2.5	[0..1]	FromToDate		<FrToDt>	+	Laiks ir grāmatvedības 'noslēgšanas' laiks. Lietojams, ja ir nepieciešams norādīt konta pārskata sākumu un beigu periodu (datumu).	Range of time between a start date and an end date for which the account statement is issued
5.1.0	[1..1]	FromDateTime		<FrDtTm>	DateTime		
5.1.1	[1..1]	ToDateTime		<ToDtTm>	DateTime		
2.10	[1..1]	Account		<Acct>	+	Informācija par kontu	Unambiguous identification of the account to which credit and debit entries are made.
1.2.0	[1..1]	Identification		<Id>		Konta numurs IBAN formātā	Only IBAN allowed in Latvia.
1.2.1	[1..1]	IBAN		<IBAN>	Identifier		
1.2.8	[0..1]	Type		<Tp>		Konta tips- Depozīta konta, Kredītlīnijas kents utt.	... For example Current, Overdraft, Saving etc.

1.2.9	[1..1]	Code	<Cd>	Code	Pielaujami blakus kolonnā minētie kontu kodi	Code Name DefinitionCACC Current Account used to post debits and credits when no specific account has been nominated.CASH CashPayment Account used for the payment of cash.CHAR Charges Account used for charges if different from the account for payment.CISH CashIncome Account used for payment of income if different from the current cash account.COMM Commission Account used for commission if different from the account for payment.LOAN Loan Account used for loans.MGLD MarginalLending Account used for a marginal lending facility.MOMA MoneyMarket Account used for money markets if different from the cash account.NREX NonResidentExternal Account used for non-resident external.ODFT Overdraft Account is used for overdrafts.ONDP OverNightDeposit Account used for overnight deposits.SACC Settlement Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system.SLRY Salary Accounts used for salary payments.SVGS Savings Account used for savings.TAXE Tax Account used for taxes if different from the account for payment.
1.2.11	[0..1]	Currency	<Ccy>	Code		
1.2.13	[0..1]	Owner	<Ownr>		Izmantojams, ja 1.3. laukā tiek norādīta pilnvarotā personā	Party that legally owns the account.
1.2.14	[0..1]	Name	<Nm>	Text	Vārds/nosaukums vai cita informācija, kas neapšaubāmi identificē konta īpašnieku	Name by which a party is known and which is usually used to identify that party.
1.2.26	[0..1]	Identification	<Id>			Unique and unambiguous identification of a party.
1.2.27	{Or	[1..1]	OrganisationIdentification	<OrgId>		

1.2.28		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).
1.2.29		[0..n]	Other	<Othr>			
1.2.30		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
1.2.31		[0..1]	SchemeName	<SchmeNm>			
1.2.32		[1..1]	Code	<Cd>	Code		
1.2.35	Or}	[1..1]	PrivateIdentification	<PrvtId>			
1.2.41		[0..n]	Other	<Othr>			
1.2.42		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
1.2.43		[0..1]	SchemeName	<SchmeNm>			
1.2.44		[1..1]	Code	<Cd>	Code		
1.2.56		[0..1]	Servicer	<Svcr>		Norādāma informācija par (trešo) pusi, kura apkalpo kontu- pārvalda grāmatvedības ierakstus, seko konta bilancei, kā arī sniedz informāciju.	Party that manages the account on behalf of the account owner, that is manages the registration and booking of entries on the account, calculates balances on the account and provides information about the account.
1.2.57		[1..1]	FinancialInstitutionIdentification	<FinInstnId>		Finanšu institūcijas identifikators	Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised scheme.
1.2.58		[0..1]	BIC	<BIC>	Identifier	Bankas BIC 8 vai 11 simboli	BIC Identifier 8 or 11 symbols
1.2.64		[0..1]	Name	<Nm>	Text		
2.11		[0..1]	RelatedAccount	<RltdAcct>	+	Grupas konta gadījumā šo lauku var izmantot lai norādītu nākamā līmeņa konta numuru. <i>Usage:</i> In case if Group account is used, this tag can be used to indicate the next level account.	Identifies the parent account of the account for which the statement has been issued.
1.1.0		[1..1]	Identification	<Id>			

1.1.1		[1..1]	IBAN	<IBAN>	Identifier		
1.1.11		[0..1]	Currency	<Ccy>	Code	<p><i>Piezīme:</i> Valūta jānorāda tikai gadījumā, konta pārskats/izraksts attiecas uz multivalūtu kontu</p>	<p>Identification of the currency in which the account is held.</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p>
2.12		[0..n]	Interest	<Intrst>		<p>Šo lauku var izmantot gadījumā, ja sūta izrakstu par kredita kontiem (2.10 - 1.2.9 kodi LOAN; ODFT; SVGS un citi).</p> <p>Par šī lauka izmantošanu jāvienojas ar banku</p>	<p>Set of elements used to provide general interest information that applies to the account at a particular moment in time.</p> <p>Usage of this should be bilaterally agreed between parties.</p>
2.13		[0..1]	Type	<Tp>			
2.14		[1..1]	Code	<Cd>	Code	INDY vai OVRN	INDY vai OVRN
2.16		[0..n]	Rate	<Rate>		Elementu kopums priekš procentu likmes norādīšanas	Set of elements used to qualify the interest rate.
2.17		[1..1]	Type	<Tp>			
2.18	{Or	[1..1]	Percentage	<Pctg>	Rate		
2.19	Or}	[1..1]	Other	<Othr>	Text		
2.23		[1..n]	Balance	<Bal>		Elementu kopums bilances skaitliskai attēlošanai konkrētajā laika posmā	Set of elements used to define the balance as a numerical representation of the net increases and decreases in an account at a specific point in time.
2.24		[1..1]	Type	<Tp>		Bilances tips (pieejamais; iegrāmatotais atlikums utt.)	Specifies the nature of a balance.
2.25		[1..1]	CodeOrProprietary	<CdOrPrtry>			

2.26	[1..1]	Code	<Cd>	Code	Izraksts ir par noslēgtu periodu, tāpēc bankas izmanto dažādus atļautos kodus no ISO saraksta. Obligātie kodi: OPBD = Sākuma atlikums ar datumu, kurā sākuma atlikums ir fiksēts; CLBD = Beigu atlikums. Par pārējo kodu izmantošanu jāvienojas individuāli.	<u>Required balance types:</u> OPBD = OpeningBooked with date on which the opening balance was determined; CLBD = ClosingBooked <u>Required balance sub type</u> in paginated statement message: INTM = Intermediate Used together with OPBD and CLBD balance type codes to indicate intermediate characteristic of the balance <u>Bilaterally determined balance types:</u> PRCD = PreviouslyClosedBooked with date of the previous customer statement message for the account CLAV = ClosingAvailable FWAV= ForwardAvailable
2.28	[0..1]	SubType	<SubTp>			
2.29	[1..1]	Code	<Cd>	Code	INTM = Intermediate (starpzīņojums). Numurētiem pārskatos/izrakstos INTM jālieto kopā ar OPBD un CLBD bilances tipu kodiem, lai parādītu zīnojuma sākumu un beigas. Pārējie kodi izmantojami savstarpeji vienojoties klientam ar kredītiesādi.	INTM = Intermediate For paginated messages INTM is to be used together with OPBD and CLBD balance type codes to indicate intermediate characteristic of the balance. Other type codes usage is bilaterally determined by parties involved.
2.31	[0..1]	CreditLine	<CdtLine>		Kredītlīnija/Overdrafts	Set of elements used to provide details on the credit line
2.32	[1..1]	Included	<Incl>	Indicator	Norāda vai kredītlīnija tiek ierēķināta bilancē (vērtības True/False) Usage: If not present, credit line is not included in the balance amount. One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False	Indicates whether or not the credit line is included in the balance. Usage: If not present, credit line is not included in the balance amount. One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False
2.33	[0..1]	Amount	<AmtCcy="AAA">	Amount	Kredītlīnijas/Overdrafta summa un valūta	Amount of money of the credit line

2.34		[1..1]	Amount	<AmtCcy="AAA">	Amount	Konta bilance	Amount of money of the cash balance.
2.35		[1..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda kredīta vai debeta bilanci. CRDT=bilances atlikums palielinās; DBIT=bilances atlikums samazinās. <i>Piezīme:</i> Nulles atlikums uzskatāms par pozitīvu atlikumu.	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.
2.36		[1..1]	Date	<Dt>	+		
4.1.0		[1..1]	Date	<Dt>	DateTime		
2.43		[0..1]	TransactionsSummary	<TxSummry>			
2.49		[0..1]	TotalCreditEntries	<TtlCdtNtries>		Kopējā kredīta ierakstu summa un skaits	Specifies the total number and sum of credit entries.
2.50		[0..1]	NumberOfEntries	<NbOfNtries>	Text	ierakstu skaits	Number of individual entries included in the report.
2.51		[0..1]	Sum	<Sum>	Quantity	Kopējā ierakstu summa	Total of all individual entries included in the report.
2.52		[0..1]	TotalDebitEntries	<TtlDbtNtries>		Kopējā debeta ierakstu summa un skaits	Specifies the total number and sum of debit entries.
2.53		[0..1]	NumberOfEntries	<NbOfNtries>	Text	ierakstu skaits	Number of individual entries included in the report.
2.54		[0..1]	Sum	<Sum>	Quantity	Kopējā ierakstu summa	Total of all individual entries included in the report.
2.76		[0..n]	Entry	<Ntry>		Lauks var būt tukšs, ja kontā nav bijis darījumu. <i>Piezīme.</i> Darījumu uzskaites sadaļa. Katrs darījums uzskaitās atsevišķi šādi ieraksti failā var būt no 0 (nav darījumu) līdz noteiktam daudzumam kuru banka spēj izdot vienā failā.	Can be absent if no movement for the account. For reporting single transaction or batch or collection of batches. If there are no transactions, we can send zeroes in header, and don't include this section at all
2.77		[0..1]	EntryReference	<NtryRef>	Text	Unikāla ieraksta reference viena izraksta ietvaros. <i>Piezīme.</i> Var būt ieraksta kārtas numurs	Unique reference for the entry <i>within one statement.</i> <i>Remark:</i> Can also be number of an entry.
2.78		[1..1]	Amount	<AmtCcy="AAA">	Amount	Summa konta valūtā	Amount in the currency of the account reported. Note: This amount can be Zero.

2.79	[1..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredīta vai Debeta (CRDT vai DBIT)	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.
2.80	[0..1]	ReversallIndicator	<RvslInd>	Indicator	Norāda uz to vai darījums ir reverss (atgrieziem/atsaukiem darījumiem). <i>Piezīme:</i> laiks tie izmantots tikai tad, ja ieraksts ir saistīts ar atgrieztu darījumu.	Indicates whether or not the entry is the result of a reversal. Usage: This element should only be present if the entry is the result of a reversal. If the CreditDebitIndicator is CRDT and ReversallIndicator is Yes, the original operation was a debit entry. If the CreditDebitIndicator is DBIT and ReversallIndicator is Yes, the original operation was a credit entry. Data Type: One of the following TrueFalseIndicator values must be used: MeaningWhenTrue: True MeaningWhenFalse: False
2.81	[1..1]	Status	<Sts>	Code	Izrakstā izmantojams tikai BOOK, jo camt.053 izraksts satur tikai pabeigus darījumus.	Booked for End of Cycle statement: BOOK = Booked is required.
2.82	[0..1]	BookingDate	<BookgDt>	+	Laiks, kad kontā izdarīts grāmatojums.	Date when an entry is posted to an account on the account servicer's books.
4.1.0	[1..1]	Date	<Dt>	DateTime		Specified date.
	[0..1]	ValueDate	<ValDt>	+	Var tik norādīts darījumiem ar pagātnes vai nākotnes value date.	
4.1.0	[1..1]	Date	<Dt>	DateTime		Specified date.

2.84	[0..1]	AccountServicerReference	<AcctSvcrRef>	Text	Unikāls darījuma identifikators bankas ietvaros (piem. arhivārais Nr.) <i>Piezīme:</i> kad viens un tas pats ieraksts tiek parādīts gan camt.052, gan camt.053- tiem ir jāsakrīt	Unique reference as assigned by the account servicing institution to unambiguously identify the entry. <i>Recommendation:</i> When the same booked entry is reported in both the camt.052 or camt.054, the Account Service reference should be the same as reported in camt.053.
2.91	[1..1]	BankTransactionCode	<BkTxCd>		Vismaz vienam (Domain/Proprietary) jābūt izmantotam	Set of elements used to fully identify the type of underlying transaction resulting in an entry. Domain and/or proprietary may be provided. At least one must be provided.
2.92	[0..1]	Domain	<Domn>		Izmantoti atbilstoši ISO banku transakciju kodi	Recommendation suggested that standard BTC are used as first priority
2.93	[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.94	[1..1]	Family	<Fmly>			http://www.iso20022.org/external_code_list.page
2.95	[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.96	[1..1]	SubFamilyCode	<SubFmlyCd>	Code		http://www.iso20022.org/external_code_list.page
2.97	[0..1]	Proprietary	<Prtry>		Vieta kur var izmantot pašreiz lietotos kodus	<i>Remark:</i> For bank or community specific transaction coding
2.98	[1..1]	Code	<Cd>	Text		<i>Remark:</i> Code format is depending on the issuer. It may be a composite code.
2.99	[0..1]	Issuer	<Issr>	Text		Value samples (not exhausted): BAI = BAI Code SWIFT = Swift Code BBA = Belgian Code CFONB = French Code FFFS = Finnish Code ZKA = German Code GVC = German Code AEB = Spanish Code DBA = Danish Code Also other values available such as bank name

2.135	[0..n]	EntryDetails	<NtryDtls>		Ja netiek lietota Pain.001 batch Booking iespēja, tad katram Entry (lauks 2.76) saistīts ir tikai viens lauks EntryDetails	This provides a breakdown of the transaction details when the entry is 'batched'. If the entry is not batched and transaction details are to be reported, then transaction details must only occur once.
2.136	[0..1]	Batch	<Btch>		Izmantojams transakciju detaļu norādišanai faila maksājumu gadījuma	Set of elements used to provide details on batched transactions
2.137	[0..1]	MessageIdentification	<MsgId>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 1.1 no "pain.001.001.03"	Point to point reference, as assigned by the sending party, to unambiguously identify the batch of transactions
2.138	[0..1]	PaymentInformationIdentification	<PmtInfId>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 2.1 no "pain.001.001.03"	Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message
2.139	[0..1]	NumberOfTransactions	<NbOfTxns>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 2.4 no "pain.001.001.03"	Number of individual transactions included in the batch
2.140	[0..1]	TotalAmount	<TtlAmtCcy="AAA">	Amount	<i>Piezīme:</i> Zinojuma elementa numurs 2.5 no "pain.001.001.03"	Total amount of money reported in the batch entry
2.141	[0..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredīta vai Debēta (CRDT vai DBIT) Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.	
2.142	[0..n]	TransactionDetails	<TxDtls>			Set of elements used to provide information on the underlying transaction(s)
2.143	[0..1]	References	<Refs>			Set of elements used to provide the identification of the underlying transaction
2.144	[0..1]	MessageIdentification	<MsgId>	Text		Point to point reference, as assigned by the instructing party of the underlying message
2.145	[0..1]	AccountServicerReference	<AcctSvcrRef>	Text	Norādāma konkrēta maksājuma, kas iekļauts failā, reference.	Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction

2.146		[0..1]	PaymentInformationIdentification	<PmtInfId>	Text		Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message
2.147		[0..1]	InstructionIdentification	<InstrId>	Text	Unikāls transakcijas identifikators. <i>Piezīme:</i> Zinojuma elementa numurs 2.29 no "pain.001.001.03"	Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.
2.148		[0..1]	EndToEndIdentification	<EndToEndId>	Text	Unikāls maksājuma identifikators, kas tiek nodots caur visu maksājuma kēdi nemainīts. Tieki pārsūtīts tālāk tikai SEPA maksājumos. Laukā norādītais identifikators paredzēts, lai klients-klients posmā identificētu maksājumu. Ja netiek padots pain.001, tad atpakaļ padod NOT PROVIDED. Ne-SEPA maksājumos šis laiks tiek ignorēts. <i>Piezīme:</i> Zinojuma elementa numurs 2.30 no "pain.001.001.03"	Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. <i>Usage:</i> The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain. Comment: The end-to-end identification must be reported when it is known by the reporting bank. For SEPA the EndToEndId can be 'NOTPROVIDED'.
2.149		[0..1]	TransactionIdentification	<TxId>	Text		
2.150		[0..1]	MandateIdentification	<MndtId>	Text	Priekš SEPA tiešā debeta darījumiem <i>Comment:</i> For reporting SEPA Direct Debits, as appropriate	Unique identification, as assigned by the creditor, to unambiguously identify the mandate.
2.153		[0..1]	Proprietary	<Prtry>		Reference, kas attiecināma uz konkrēto maksājumu	Proprietary reference related to the underlying transaction.
2.154		[1..1]	Type	<Tp>	Text		

2.155		[1..1]	Reference	<Ref>	Text		
2.156		[0..1]	AmountDetails	<AmtDtls>	+		<p>Set of elements providing detailed information on the original amount.</p> <p><i>Usage:</i> This component (on transaction level) should be used in case booking is for a single transaction and the original amount is different from the entry amount. It can also be used in case individual original amounts are provided in case of a batch or aggregate booking.</p> <p><i>Comment:</i> All Amount Details are in all cases given on the Transaction Details level on single and batch bookings. For consistency purposes Entry/Amount information is repeated at TransactionDetails/AmountDetails/TransactionAmount.</p>
2.1.0		[0..1]	InstructedAmount	<InstdAmt>		Izmanto: -> lai norādītu sākotnējo summu, ja maksājums uzsākts citā valūtā; -> ja maksājums ir tajā pašā valūtā, lai norādītu bruto summu (t.i., summu pirms komisiju ieturēšanas). Piemēram, starpbanku MT103 ziņojuma šī summa ziņo par 33.b lauku saturu. Norādītās summas var izlaist tādā gadījumā, ja nav ieturēta komisija vai arī maksājumu apstrādes procesā nav notikusi konvertācija.	<p><i>Usage:</i> Used for original amount in original currency and is the gross value (i.e. prior to application of charges) in same currency situations. For example in the inter-bank MT103 message this amount reports the 33B field contents. Instructed Amount may be omitted in the case when there are no charges or no FX. In FX cases the booked transaction FX information can be found with TransactionAmount. When account servicing bank is receiving a transaction via MT103, it might contain other FX information of sender bank FX operation. This is only in the situation of original payment initiation done with Equivalent amount.</p>
2.1.1		[1..1]	Amount	<AmtCcy="AAA">	Amount		
2.1.2		[0..1]	CurrencyExchange	<CcyXchg>			
2.1.3		[1..1]	SourceCurrency	<SrcCcy>	Code	Valūta, no kurās tiek veikta konvertācija	Currency from which an amount is to be converted in a currency conversion.

2.1.4		[0..1]	TargetCurrency	<TrgtCcy>	Code	Valūta, uz kuru tiek veikta konvertācija	Currency into which an amount is to be converted in a currency conversion.
2.1.5		[0..1]	UnitCurrency	<UnitCcy>	Code		
2.1.6		[1..1]	ExchangeRate	<XchgRate>	Rate		
2.1.7		[0..1]	ContractIdentification	<CtrctId>	Text	<i>Piezīme:</i> Zinojuma elementa numurs 2.50 no "pain.001.001.03"	Unique identification to unambiguously identify the foreign exchange contract.
2.1.9		[0..1]	TransactionAmount	<TxAmt>		Norādām transakciju konta valūtā un par attiecīgo summu	<p>Amount of the underlying transaction.</p> <p><i>Remark:</i> EPC Mandated for SEPA payments.</p> <p>Recommendation: This amount is to be used for matching and aggregation purpose and it is used in all cases when AmountDetails structure is used. It is always in the currency of the account reported and the Entry Amount and populated in all Transaction Details—cases when AmountDetails structure is used.</p>

						It is the net amount of the underlying transaction including charges expressed in the currency of the posting account. This will apply both Single Bookings and Batch Bookings with underlying transactions. This amount indicates the value that has been debited from or credited to reported bank account (booked or posted amount). Note: this information may be duplicate with Entry/Amount if the single booking is in the same currency as reported account currency is.
2.1.10	[1..1]	Amount	<AmtCcy="AAA">	Amount		
2.1.11	[0..1]	CurrencyExchange	<CcyXchg>			
2.1.12	[1..1]	SourceCurrency	<SrcCcy>	Code		
2.1.13	[0..1]	TargetCurrency	<TrgtCcy>	Code		
2.1.14	[0..1]	UnitCurrency	<UnitCcy>	Code		
2.1.15	[1..1]	ExchangeRate	<XchgRate>	Rate		
2.1.16	[0..1]	ContractIdentification	<CtrctId>	Text		
2.1.17	[0..1]	QuotationDate	<QtnDt>	Datetime		
2.163	[0..1]	BankTransactionCode	<BkTxCd>		Piezīme: Satur to pašu informāciju, kas 2.91. Taču tā var būt atšķirīga Batch Booking gadījumā.	
2.164	[0..1]	Domain	<Domn>			Recommendation suggested that standard BTC are used as first priority
2.165	[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.166	[1..1]	Family	<Fmly>			http://www.iso20022.org/external_code_list.page
2.167	[1..1]	Code	<Cd>	Code		http://www.iso20022.org/external_code_list.page
2.168	[1..1]	SubFamilyCode	<SubFmlyCd>	Code		http://www.iso20022.org/external_code_list.page
2.169	[0..1]	Proprietary	<Prtry>			Remark: For bank or community specific transaction coding

2.170		[1..1]	Code	<Cd>	Text		Remark: Code format is depending on the issuer. It may be a composite code.
2.171		[0..1]	Issuer	<Issr>	Text		
2.172		[0..n]	Charges	<Chrgs>			
2.173		[0..1]	TotalChargesAndTaxAmount	<TtlChrgsAndTaxArntCcy="AAA">	Amount		
2.174		[1..1]	Amount	<AmtCcy="AAA">	Amount		
2.175		[0..1]	CreditDebitIndicator	<CdtDbtInd>	Code	Norāda uz to vai darījums uz konta ir Kredita vai Debeta (CRDT vai DBIT)	Indicates whether the balance is a credit or a debit balance. CRDT=Credit Operation is an increase. DBIT=Debit Operation is a decrease. Usage: A zero balance is considered to be a credit balance.
2.176		[0..1]	Type	<Tp>			Specifies the type of charge
2.177		[1..1]	Code	<Cd>	Code		BRKF - Brokerage Fee COMM - Commission. Used in case of incoming cardpayment
2.181		[0..1]	Party	<Pty>	+		Party that takes the transaction charges or to which the transaction charges are due
6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		BIC of financial institution debiting the charges If not informed, the charge is taken by creditor bank.
6.1.7		[0..1]	Name	<Nm>	Text		
2.199		[0..1]	RelatedParties	<RltdPties>			
2.200		[0..1]	InitiatingParty	<InitgPty>	+	Ienākošajiem maksājumiem tiek pievienots, ja ir pieejams.	For incoming payments is reported if available. For outgoing payments: Initiating

						Izejošajiem maksājumiem: Initiating party <InitgPty> no pain.001, ja ir pieejams (lauks 1.8)	party <InitgPty> from pain.001, if available (tag 1.8)
9.1.0		[0..1]	Name	<Nm>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13		[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18		[1..1]	Code	<Cd>	Code		
2.201		[0..1]	Debtor	<Dbtr>	+	Ienākošajiem maksājumiem: Nosaukums, adrese un identifikators tiek norādīti, ja ir pieejami. Izejošajiem maksājumiem: Netiek lietots (informācija tieka parādīta blokā Account Owner)	For incoming payments name, address and ID are reported if available. For outgoing payments: Not used
9.1.0		[0..1]	Name	<Nm>	Text		
9.1.1		[0..1]	PostalAddress	<PstlAdr>			
9.1.2		[0..1]	AddressType	<AdrTp>	Code		
9.1.3		[0..1]	Department	<Dept>	Text		
9.1.4		[0..1]	SubDepartment	<SubDept>	Text		
9.1.5		[0..1]	StreetName	<StrtNm>	Text		
9.1.6		[0..1]	BuildingNumber	<BldgNb>	Text		
9.1.7		[0..1]	PostCode	<PstCd>	Text		
9.1.8		[0..1]	TownName	<TwnNm>	Text		
9.1.9		[0..1]	CountrySubDivision	<CtrySubDvsn>	Text		
9.1.10		[0..1]	Country	<Ctry>	Code		

9.1.11		[0..7]	AddressLine	<AdrLine>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or}	[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18	{Or}	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļa maksātāja kods, šis laiks satur TXID. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page ExternalOrganisationIdentification1Code	If tax payer ID provided, then TXID indicated. Valid codes available at http://www.iso20022.org/external_code_list.page ExternalOrganisationIdentification1Code
9.1.19	Or{}}	[1..1]	Proprietary	<Prtry>	Text		
9.1.20		[0..1]	Issuer	<Issr>	Text		
9.1.21	Or{}	[1..1]	PrivateIdentification	<PrvtId>			
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>			
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text		
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		

9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis laiks satur NIDN. Pieļautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	If personal code provided, then NIDN indicated. Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalPersonIdentification1Code
9.1.31	Or{}	[1..1]	Proprietary	<Prtry>	Text		
9.1.32		[0..1]	Issuer	<Issr>	Text		
2.202		[0..1]	DebtorAccount	<DbtrAcct>	+	lenākošajiem maksājumiem: konts tiek norādīts, ja ir pieejams. Izejošajiem maksājumiem: Netiek lietots (informācija tiek parādīta kontā pārskata/izraksta līmenī)	For incoming payments account is reported if available. For outgoing payments: Not used
1.1.0		[1..1]	Identification	<Id>			
1.1.1	{Or	[1..1]	IBAN	<IBAN>	Identifier		
1.1.2	Or{}	[1..1]	Other	<Othr>			
1.1.3		[1..1]	Identification	<Id>	Text		
1.1.4		[0..1]	SchemeName	<SchmeNm>			

1.1.5		[1..1]	Code	<Cd>	Code		
2.203		[0..1]	UltimateDebtor	<UltmtDbtr>	+	Tikai SEPA maksājumiem. Tieki norādīts gadījumos ja sanemts ienākošajā maksājumā, vai Maksātājs norādījis izējošajā maksājumā. Vērtība no laukiem 2.70 vai 2.23, ja maksājums iesūtīts ar pain.001 un ir norādīts	Ultimate party that owes an amount of money to the (ultimate) creditor. EPC mandated for SEPA Payment. In instances where the ReversalIndicator <Rvslnd> is TRUE, the Ultimate Creditor and Ultimate Debtor must be the same as the Ultimate Creditor and Ultimate Debtor of the original entry.
9.1.0		[0..1]	Name	<Nm>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or	[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18		[1..1]	Code	<Cd>	Code		
9.1.21	Or}	[1..1]	PrivatIdentification	<PrvtId>			
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>			
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text		
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		
9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30		[1..1]	Code	<Cd>	Code		
2.204		[0..1]	Creditor	<Cdtr>	+	Ienākošiem maksājumiem tiek norādīts kā konta	For outgoing payments details are taken from tag 2.79 from pain.001.

						Īpašnieks. Izejošiem maksājumiem norāda klienta doto informāciju (vērtība no lauka 2.79, ja maksājums iesūtīts ar pain.001)	For incoming payments: Not used.
9.1.0		[0..1]	Name	<Nm>	Text	Pārskata/izraksta lauks 2.10; apakšlauks 1.2.13	
9.1.1		[0..1]	PostalAddress	<PstlAdr>			
9.1.10		[0..1]	Country	<Ctry>	Code		
9.1.11		[0..7]	AddressLine	<AdrLine>	Text		
9.1.12		[0..1]	Identification	<Id>			
9.1.13	{Or	[1..1]	OrganisationIdentification	<OrgId>			
9.1.14		[0..1]	BICOrBEI	<BICOrBEI>	Identifier		Code allocated to organisations by the ISO 9362 Registration Authority, under an international identification scheme, as described in the latest version of the standard ISO 9362 Banking (Banking telecommunication messages, Bank Identifier Codes).
9.1.15		[0..n]	Other	<Othr>			
9.1.16		[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID
9.1.17		[0..1]	SchemeName	<SchmeNm>			
9.1.18	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts nodokļu maksātāja kods, šis lauks satur TXID.	If tax payer ID provided, then TXID indicated. Valid codes available at http://www.iso20022.org/external_

					Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalOrganisationIdentification1Code	code_list.page in worksheet ExternalOrganisationIdentification1Code	
9.1.19	Or{}	[1..1]	Proprietary	<Prtry>	Text		
9.1.20		[0..1]	Issuer	<Issr>	Text		
9.1.21	Or{}	[1..1]	PrivatIdentification	<PrvtId>		Privātpersonas Identifikators	
9.1.22		[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		Informācija par dzimšanas vietu un laiku	
9.1.23		[1..1]	BirthDate	<BirthDt>	DateTime		
9.1.25		[1..1]	CityOfBirth	<CityOfBirth>	Text	Dzimšanas vietas valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	
9.1.26		[1..1]	CountryOfBirth	<CtryOfBirth>	Code		
9.1.27		[0..n]	Other	<Othr>			
9.1.28		[1..1]	Identification	<Id>	Text	Privātpersonas personas kods E.g. personal code of debtor who is a private person	
9.1.29		[0..1]	SchemeName	<SchmeNm>			
9.1.30	{Or	[1..1]	Code	<Cd>	Code	Identifikācijas shēmas kods. Ja tiek norādīts personas kods, šis laiks satur NIDN. Pielautie kodi pieejami sarakstā http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	If personal code provided, then NIDN indicated. Valid codes available at http://www.iso20022.org/external_code_list.page in worksheet ExternalPersonIdentification1Code

9.1.31	Or{}	[1..1]	Proprietary	<Prtry>	Text	Identifikācijas shēmas nosaukums brīvā tekstā	
9.1.32		[0..1]	Issuer	<Issr>	Text		
9.1.33		[0..1]	CountryOfResidence	<CtryOfRes>	Code	Valsts kods no http://www.iso.org/iso/country_codes/iso_3166_code_lists/country_names_and_code_elements.htm	
2.205		[0..1]	CreditorAccount	<CdtrAcct>	+	<p>Ienākošiem maksājumiem tiek norādīts konta pārskata/izraksta līmenī (lauks 2.10). Izejošiem maksājumiem norāda klienta doto informāciju (vērtība no lauka 2.80, ja maksājums iesūtīts ar pain.001)</p> <p>Obligāti jālieto IBAN priekš SEPA maksājumiem</p>	<p>For outgoing payments account is taken from tag 2.80 from pain.001. IBAN usage mandatory for SEPA payments</p> <p>For incoming payments: Not used.</p>
1.1.0		[1..1]	Identification	<Id>			
1.1.1	{Or	[1..1]	IBAN	<IBAN>	Identifier		
1.1.2	Or{}	[1..1]	Other	<Othr>		Izmanto, ja nav pieejams IBAN.	If IBAN not used
1.1.3		[1..1]	Identification	<Id>	Text		
1.1.4		[0..1]	SchemeName	<SchmeNm>			
1.1.5		[1..1]	Code	<Cd>	Code		
2.206		[0..1]	UltimateCreditor	<UltmtCdtr>	+	Tikai SEPA maksājumiem. Tieki norādīti gadījumos ja sanemts ienākošajā maksājumā, vai Maksātājs norādījis izeošajā	Ultimate party to which an amount of money is due. EPC Mandated for SEPA Payments. In instances where the ReversalIndicator <Rsllnd> is TRUE, the Ultimate

						maksājumā. <i>Piezīme:</i> vērtība no lauka 2.81, ja maksājums iesūtīts ar pain.001	Creditor and Ultimate Debtor must be the same as the Ultimate Creditor and Ultimate Debtor of the original entry.
9.1.0	[0..1]	Name	<Nm>	Text			
9.1.12	[0..1]	Identification	<Id>				
9.1.13 {Or	[1..1]	OrganisationIdentification	<OrgId>				
9.1.14	[0..1]	BICOrBEI	<BICOrBEI>	Identifier			
9.1.15	[0..n]	Other	<Othr>				
9.1.16	[1..1]	Identification	<Id>	Text	Uzņēmuma reģistrācijas numurs vai nodokļu maksātāja numurs	Registration number or TAX ID	
9.1.17	[0..1]	SchemeName	<SchmeNm>				
9.1.18	[1..1]	Code	<Cd>	Code			
9.1.21 Or}	[1..1]	PrivateIdentification	<PrvtId>				
9.1.22	[0..1]	DateAndPlaceOfBirth	<DtAndPlcOfBirth>				
9.1.23	[1..1]	BirthDate	<BirthDt>	DateTime			
9.1.25	[1..1]	CityOfBirth	<CityOfBirth>	Text			
9.1.26	[1..1]	CountryOfBirth	<CtryOfBirth>	Code			
9.1.27	[0..n]	Other	<Othr>				
9.1.28	[1..1]	Identification	<Id>	Text	Privātpersonas personas kods	E.g. personal code of debtor who is a private person	
9.1.29	[0..1]	SchemeName	<SchmeNm>				
9.1.30	[1..1]	Code	<Cd>	Code			
2.211	[0..1]	RelatedAgents	<RltdAgts>				
2.212	[0..1]	DebtorAgent	<DbtrAgt>	+	Izmanto tikai ienākošajiem maksājumiem, lai norādītu maksātāja banku.	EPC Mandated for SEPA CT and DD. One of the following must be provided - BIC or Clearing System Member or Name. In instances where the ReversalIndicator <RvslInd> is TRUE, the Creditor Agent and Debtor Agent must be	

							the same as the Creditor Agent and Debtor Agent of the original entry.
6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		
6.1.7		[0..1]	Name	<Nm>	Text		
2.213		[0..1]	CreditorAgent	<CdtrAgt>	+	<p>Izmanoto tikai izeošajiem maksājumiem, lai norādītu saņēmējbanku.</p> <p><i>Piezīme:</i> vērtība no lauka 2.77, ja maksājums iesūtīts ar pain.001</p>	<p>EPC Mandated for SEPA CT and DD. In instances where the ReversalIndicator <Rvslnd> is TRUE, the Creditor Agent and Debtor Agent must be the same as the Creditor Agent and Debtor Agent of the original entry.</p>
6.1.0		[1..1]	FinancialInstitutionIdentification	<FinInstnId>			
6.1.1		[0..1]	BIC	<BIC>	Identifier		
6.1.2		[0..1]	ClearingSystemMemberIdentification	<ClrSysMmbld>			
6.1.3		[0..1]	ClearingSystemIdentification	<ClrSysId>			
6.1.4		[1..1]	Code	<Cd>	Code		
6.1.6		[1..1]	MemberIdentification	<Mmbld>	Text		
6.1.7		[0..1]	Name	<Nm>	Text		
6.1.8		[0..1]	PostalAddress	<PstlAdr>			
6.1.17		[0..1]	Country	<Ctry>	Code		
6.1.18		[0..7]	AddressLine	<AdrLine>	Text		
2.224		[0..1]	Purpose	<Purp>		<p><i>Piezīme:</i> vērtība no lauka 2.86, ja maksājums iesūtīts ar pain.001</p>	<p><i>Remark:</i> in case of outgoing value from tag 2.86 from pain.001</p>
2.225	{Or}	[1..1]	Code	<Cd>	Code		

2.226	Or}	[1..1]	Proprietary	<Prtry>	Text		
2.234		[0..1]	RemittanceInformation	<RmtInf>		<p>Piezīme: vērtība no laukā 2.98, ja maksājums iesūtīts ar pain.001</p> <p>Izņēmums: Valsts kases gadījumā šī sadāļa tiek izmantota arī EKK un ar to saistītās informācijas atspoguļošanai. Informācija, kas paredzēta laukā 2.236 (un zemāk), tiek atspoguļota laukā 2.235</p>	<p>Remark: in case of outgoing value from tag 2.98 from pain.001</p> <p>Exception: In case of StateTreasury this component is also used to display information about EKK (ECC - Economic Classification Code) and the information related to it. The information that is meant for tag 2.236 (and below) is displayed in 2.235</p>
2.235		[0..n]	Unstructured	<Ustrd>	Text	<p>Izmantojam to pašu logiku, ko maksājuma iniciēšanas failā- lauka garums ne vairāk par 140.</p> <p>Piezīme: vērtība no laukā 2.99, ja maksājums iesūtīts ar pain.001</p> <p>Izņēmums: Valsts kases gadījumā tiek izmantoti vairāki (atkārtoti) sadalas ieraksti, lai atspoguļotu nestukturēto <u>VAI</u> strukturēto informāciju, kā arī, lai atspoguļotu EKK un to pavadošo informāciju. Piemēru skatīt zemāk.</p>	<p>Length of field limited to 140 characters.</p> <p>Remark: in case of outgoing value from tag 2.99 from pain.001</p> <p>Exception: In case of StateTreasury the tag is used for several times in order to display unstructured <u>OR</u> structured information as well as EKK (ECC - Economic Classification Code) and the information related to it. Please see below for example.</p>
2.236		[0..n]	Structured	<Strd>		<p>Piezīme: vērtība no laukā 2.100, ja maksājums iesūtīts ar pain.001</p> <p>Izņēmums: Valsts kases gadījumā netiek izmantots. Ja maksājums iesūtīts ar pain.001, tad šai sadalai paredzēto informāciju attēlo laukā 2.235. pierakstā /RFB/XXXXX, kur X ir vērtība no pain.001 lauka 2.100</p>	<p>Remark: in case of outgoing value from tag 2.100 from pain.001</p> <p>Exception: In case of StateTreasury this component is not used. If payment is imported with pain.001, then the information supposed for this tag is displayed in tag 2.235 in the following format: /RFB/XXXXX, where X is the value from tag 2.100 in pain.001</p>
2.237		[0..n]	ReferredDocumentInformation	<RfrdDocInf>			
2.238		[0..1]	Type	<Tp>			
2.239		[1..1]	CodeOrProprietary	<CdOrPrtry>			
2.240	{Or	[1..1]	Code	<Cd>	Code		

2.241	Or}	[1..1]	Proprietary	<Prtry>	Text		
2.243		[0..1]	Number	<Nb>	Text		
2.244		[0..1]	RelatedDate	<RltdDt>	DateTime		
2.245		[0..1]	ReferredDocumentAmount	<RfrdDocAmt>			
2.246		[0..1]	DuePayableAmount	<DuePyblAmtCcy="AAA">	Amount		
2.248		[0..1]	CreditNoteAmount	<CdtNoteAmtCcy="AAA">	Amount		
2.255		[0..1]	RemittedAmount	<RmtdAmtCcy="AAA">	Amount		
2.256		[0..1]	CreditorReferenceInformation	<CdtrRefInf>		Piezīme: vērtība no lauka 2.120, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.120 from pain.001
2.257		[0..1]	Type	<Tp>		Piezīme: vērtība no lauka 2.121, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.121 from pain.001
2.258		[1..1]	CodeOrProprietary	<CdOrPrtry>		Piezīme: vērtība no lauka 2.122, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.122 from pain.001
2.259		[1..1]	Code	<Cd>	Code	Piezīme: vērtība no lauka 2.123, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.123 from pain.001
2.261		[0..1]	Issuer	<Issr>	Text	Piezīme: vērtība no lauka 2.125, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.125 from pain.001
2.262		[0..1]	Reference	<Ref>	Text	Piezīme: vērtība no lauka 2.126, ja maksājums iesūtīts ar pain.001	Remark: in case of outgoing value from tag 2.126 from pain.001
2.265		[0..3]	AdditionalRemittanceInformation	<AddtlRmtInfo>	Text		
2.293		[0..1]	ReturnInformation	<Rtrlnf>		Norāda informāciju saistītu ar maksājuma atgriešanu	Report when available for return items
2.304		[0..1]	Reason	<Rsn>		Norāda maksājuma atgriešanas kodu. Kodi pieejami http://www.iso20022.org/external_code_list.page sarakstā ExternalPersonIdentification1Code	Specifies Reason for Return. Valid codes available at http://www.iso20022.org/external_code_list.page in a worksheet ExternalReturnReason1Code

2.305	{Or}	[1..1]	Code	<Cd>	Code		
2.306	Or}	[1..1]	Proprietary	<Prtry>	Text		
2.307		[0..n]	AdditionalInformation	<AddtlInf>	Text		
2.313		[0..1]	AdditionalTransactionInformation	<AddtlTxlnf>	Text	<p>Priekš EKK koda norādišanas komercbankās (Valsts Kases gadījumā skatīt aprakstu pie 2.234)</p> <p><i>Piemērs: //EKK/12345/</i></p>	<p>To be used to indicate EKK by banks (In case of State Treasury see description under 2.234)</p> <p><i>Example: //EKK/12345/</i></p>

EKK kodu lietošanas piemērs Valsts Kasē

<RmtInfs>

<Ustrd>/RFB/RF0243256216</Ustrd>
<!-- ja no PAIN 0001 ienāk kā Strd, tad CAMT attēlo Ustrd -->
<Ustrd>/šeit tiek ierakstīts maksājuma mērķis nestrukturētā veidā</Ustrd>
<!-- ja no PAIN 001 ienāk kā Ustrd, tad CAMT attēlo Ustrd -->
<Ustrd>/EKKACC/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
<Ustrd>/EKKACC/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
<Ustrd>/EKKPMT/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
<Ustrd>/EKKPMT/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
<Ustrd>/EKKLOC/CRDT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>
<Ustrd>/EKKLOC/DBIT/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/21499/1234567891.00/</Ustrd>

</RmtInfs>

Konta izraksta ziņojuma paraugs

```
<?xml version="1.0" encoding="UTF-8"?>
<Document>
  <BkToCstmrStmt>
    <GrpHdr>
      <MsgId>STMT20130710193521</MsgId>
      <CreDtTm>2001-12-17T09:30:47Z</CreDtTm>
    </GrpHdr>
    <Stmt>
      <Id>5074322222537</Id>
      <CreDtTm>2001-12-17T09:30:47Z</CreDtTm>
      <FrToDt>
        <FrDtTm>2001-12-17T09:30:47Z</FrDtTm>
        <ToDtTm>2001-12-17T09:30:47Z</ToDtTm>
      </FrToDt>
      <Acct>
        <Id>
          <IBAN>LV12TEST000000000001</IBAN>
        </Id>
        <Ccy>USD</Ccy>
        <Svcr>
          <FinInstnId>
            <BIC>TESTLV22</BIC>
          </FinInstnId>
        </Svcr>
      </Acct>
      <Bal>
        <Tp>
          <CdOrPrtry>
            <Cd>OPBD</Cd>
          </CdOrPrtry>
        </Tp>
        <Amt Ccy="USD">500</Amt>
        <CdtDbtInd>CRDT</CdtDbtInd>
        <Dt>
          <Dt>2001-12-17</Dt>
        </Dt>
      </Bal>
      <!-- transakcija bez konvertācijas -->
      <Ntry>
```

```
<Amt Ccy="USD">3</Amt>
<CdtDbtInd>DBIT</CdtDbtInd>
<Sts>BOOK</Sts>
<BookgDt>
  <Dt>2001-12-17</Dt>
</BookgDt>
<!-- transakcijas unikālais identifikators --&gt;
&lt;AcctSvcrRef&gt;123456789&lt;/AcctSvcrRef&gt;
&lt;BkTxCd&gt;
  &lt;Domn&gt;
    &lt;Cd&gt;PMNT&lt;/Cd&gt;
    &lt;Fmly&gt;
      &lt;Cd&gt;CCRD&lt;/Cd&gt;
      &lt;SubFmlyCd&gt;FEES&lt;/SubFmlyCd&gt;
    &lt;/Fmly&gt;
  &lt;/Domn&gt;
&lt;/BkTxCd&gt;
&lt;NtryDtls&gt;
  &lt;TxDtls&gt;
    &lt;RmtInf&gt;
      &lt;Ustrd&gt;Komisijas maksā&lt;/Ustrd&gt;
    &lt;/RmtInf&gt;
  &lt;/TxDtls&gt;
&lt;/NtryDtls&gt;
&lt;/Ntry&gt;
<!-- transakcija ar konvertāciju --&gt;
&lt;Ntry&gt;
  <!-- summa konta valūtā --&gt;
  &lt;Amt Ccy="USD"&gt;128.2&lt;/Amt&gt;
  &lt;CdtDbtInd&gt;DBIT&lt;/CdtDbtInd&gt;
  &lt;Sts&gt;BOOK&lt;/Sts&gt;
  &lt;BookgDt&gt;
    &lt;Dt&gt;2001-12-17&lt;/Dt&gt;
  &lt;/BookgDt&gt;
  &lt;AcctSvcrRef&gt;12334567234&lt;/AcctSvcrRef&gt;
  &lt;BkTxCd&gt;
    &lt;Domn&gt;
      &lt;Cd&gt;PMNT&lt;/Cd&gt;
      &lt;Fmly&gt;
        &lt;Cd&gt;ICDT&lt;/Cd&gt;
        &lt;SubFmlyCd&gt;DMCT&lt;/SubFmlyCd&gt;
      &lt;/Fmly&gt;
    &lt;/Domn&gt;</pre>
```

```

</BkTxCd>
<NtryDtls>
  <TxDtls>
    <Refs>
      <EndToEndId>34</EndToEndId>
    </Refs>
    <!-- to visu bloku rādam tikai gadījumā ja bija konvertācija -->
    <AmtDtls>
      <InstdAmt>
        <!-- cik paņemts no klienta (transakcijas valūtā) -->
        <Amt Ccy="EUR">100</Amt>
      </InstdAmt>
      <TxAmt>
        <!-- summa konta valūtā -->
        <Amt Ccy="USD">128.2</Amt>
        <!-- detaļas par konvertāciju -->
        <CcyXchg>
          <!-- no kuras valūtas konvertācija -->
          <SrcCcy>USD</SrcCcy>
          <!-- uz kuru valūtu -->
          <TrgtCcy>EUR</TrgtCcy>
          <!-- pret kuras valūtas tika norādīts kurss (1 EUR = 1.282 USD) -->
          <UnitCcy>USD</UnitCcy>
          <!-- kurss -->
          <XchgRate>1.282</XchgRate>
        </CcyXchg>
      </TxAmt>
    </AmtDtls>
    <RltdPties>
      <Cdtr>
        <Nm>Gatis Egle</Nm>
        <Id>
          <PrvtId>
            <Othr>
              <Id>121212-12121</Id>
            </Othr>
          </PrvtId>
        </Id>
      </Cdtr>
      <CdtrAcct>
        <Id>
          <IBAN>LV21TEST0000000000002</IBAN>
        </Id>
      </CdtrAcct>
    </RltdPties>
  </TxDtls>
</NtryDtls>

```

```
    </CdtrAcct>
  </RltdPties>
  <RmtInf>
    <Ustrd>Parvedums ar konvertaciju</Ustrd>
  </RmtInf>
  <TxDtls>
  <NtryDtls>
  <Ntry>
  <Stmt>
  <BkToCstmrStmt>
</Document>
```

Piemērs camt.060.001.03 ziņojuma izmantošanai.

```
<?xml version="1.0" encoding="UTF-8"?>
<Document>
  <AcctRptgReq>
    <GrpHdr>
      <MsgId>687a6d87a6da876da8d68</MsgId>
      <CreDtTm>2014-03-04T12:34:56</CreDtTm>
    </GrpHdr>
    <RptgReq>
      <ReqdMsgNmId>camt.053.001.01</ReqdMsgNmId>
      <Acct>
        <!-- Obligāts bloks (pēc biznes-loģikas) -->
        <Id>
          <IBAN> LV12TEST000000000001</IBAN>
          <!-- Konta numurs -->
        </Id>
        <Ccy>EUR</Ccy>
        <!-- Valūta. Ja nav aizpildīts - pārskatā būs visas kontam pieejamas valūtas -->
      </Acct>
      <AcctOwnr>
        <!-- Obligāts bloks (pēc shēmas), bet tiek ignorēts -->
        <Pty/>
      </AcctOwnr>
      <RptgPrd>
        <FrToDt>
          <!-- Datumi no-līdz -->
          <FrDt>2013-01-01</FrDt>
          <ToDt>2013-12-31</ToDt>
        </FrToDt>
        <FrToTm>
          <!-- Laiks, no kurā interesē transakcijas (ja par visu dienu - 00:00:00) -->
          <FrTm>00:00:00</FrTm>
        </FrToTm>
        <Tp>ALLL</Tp>
      </RptgPrd>
    </RptgReq>
  </AcctRptgReq>
</Document>
```